

TOWNSHIP 24 RANGE 09 POINT IDENTIFIER # 340400

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 16 & 21

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO retracement by Levi C. Walker, Deputy Surveyor, under special instructions, dated Aug. 23, 1905, independent of but in connection with his contract # 763, dated June 20, 1905 - (DCSO records Vol. 8 Page(s) 3451)

Set a fir post, 3 ft. long, 5" sq., 24" in the ground for ¼ sec. cor. marked ¼ S16 on N and 21 on S. face; from which
A forked fir, 30" dia. bears N.8½°W. 61 lks. mkd: ¼ S16 BT
A fir, 30" dia., bears S.85°E., 18 lks., mkd: ¼ S21 BT.

Tony Hostetter - Feb. 2011 - C.S. File 65/72-5

Found: 36" Fir stump with WEYCO tag which reads "S.08½°E., 40.2 ft. 1956".
(Note) - Weyerhaeuser Company records indicate that both orig. BTs for this corner were found in 1956.
Set - 5/8" rebar w/plastic cap marked "HOSTETTER LS 1975" from which:
36" Fir stump, OBT, described above, bears N.08½°W., 40.2 ft (GLO: 30" Fir, N.08½°W, 61 lks)
New BTs- 12" Fir stump, WEYCO tag, bears: N 34°E, 30.8 ft to 12" spike, placed in root collar.
14" Fir stump, WEYCO tag, bears: S.52°E, 46.5 ft to 12" spike, placed in root collar.
16" Fir stump, WEYCO tag, bears; N 21° W, 45.5 ft to 12" spike, placed in root collar.