

TOWNSHIP 24 RANGE 09 POINT IDENTIFIER # 346700

PRIMARY CORNER DESCRIPTION South Sec. Cor Secs. 32 & 33, T23-9

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Oscar F. Thiel, under contract # 688, dated June 9, 1898 - (DCSO records Vol. 6 Page(s) 2644)

Set a sandstone 18x16x5", 12" in the ground for cor. of secs. 32 & 33, marked with 4 notches on E and 2 notches on W edges, from which,

- A Fir, 40" dia., bears N.1°E., 310 lks. marked T23S R9W S 33 BT
- A Fir, 24" dia., bears N.45°W., 26 lks., marked T23S R9W S 32 BT.

Tony Hostetter - For: Weyerhaeuser Co. - March 2007 - C.S. 65/60-24

-
- Found - 3/4" iron pipe as set by Weyerhaeuser in 1965.
40" fir stump, WEYCO tag & "W" nail, bears N.58°E, 82.0 ft to "W" nail.
36" fir stump, OBT, face evident, WEYCO tag & "W" nail, bears; N.45°W., 17.2 ft to center.
- New BTs- 11" fir, bears WEYCO tag & spike, N.87°W., 3.5 ft to spike
16" fir, bears WEYCO tag & spike, N.73°W., 39.8 ft to spike.
14" fir, bears WEYCO tag & spike, N.66°E., 21.3 ft to spike.

Note - DCSO has no record of the 1965 Weyerhaeuser corner report.