

TOWNSHIP 24 RANGE 09 POINT IDENTIFIER # 400500

PRIMARY CORNER DESCRIPTION Cor. Secs. 9, 10, 15, & 16

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO retracement by Levi C. Walker, Deputy Surveyor, under special instructions, dated Aug. 23, 1905, independent of but in connection with his contract # 763, dated June 20, 1905 - (DCSO records Vol. 8 Page(s) 3441)

-----  
Set a fir post, 3 ft. long, 4" sq. 24" in the ground, for cor. of secs. 9, 10, 15, & 16, mkd:  
T24S S10 on NE; R9W S15 on SE; S16 on SW; and S9 on NW face, with 4 notches on S & 3 notches on E edge, from which  
A fir, 40" dia. bears N.42°E. 66 lks. mkd: T24S R9W S10 BT  
A fir, 16" dia. bears S.68½°E. 59 lks. mkd T24S R9W S15 BT  
A fir, 40" dia. bears S.83°W. 13 lks. mkd: T20S R9W S16 BT  
A fir, 48" dia. bears N.45°W., 49 lks. mkd: T20S R9W S9 BT

Douglas Co. Surveyors Office - Vernon "Ray" Tracy - J. Heritage & V. Perron - Feb/March 1968 - C.S. File 54/55-11

-----  
Found - Orig. 40", now 48" Fir, alive, N.42°E., 43.6 ft. shows good scar. We do not open.  
Orig. 40", now 52" Fir, alive, S.83°W., 8.6 ft. shows good scar.  
Orig. 16", now 17" Fir snag, S.68½°E., 38.9 ft., opened previously & shows "2 S" & fragmentary scribe on decayed blaze.  
Orig. 48", now 56" Fir, alive, N.45°W., 32.3 ft. shows good scar, do not open. Rescribed in bark alongside scar. "T24S R9W S9 CS BT"  
Set - Brass cap at cor. mkd: County Surveyors T24S R9W  
Office S 9 | S 10  
1968 S 16 | S 15  
New BT - 9" Maple S.68°E., 40.4 ft. mkd: T24S R9W S15 CS BT, also "W" nail at base.  
Note - "W" nails at base of orig. BTs. Timber in this area is large. We do not scribe any other tree.