

PRIMARY CORNER DESCRIPTION W.C 1/4 Cor. Secs. 15 & 22

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO retracement by Levi C. Walker, Deputy Surveyor, under special instructions, dated Aug. 23, 1905, independent of but in connection with his contract # 763, dated June 20, 1905 - (DCSO records Vol. 8 Page(s) 3439)

A fir, 15" dia., for ¼ sec. cor. mkd: ¼ S 15 on N & 22 on S face; from which

 A fir, 14" dia., bears N.44°E., 34 lks., mkd: ¼ S15 BT.

 A fir, 16" dia., bears S.37°W., 15 lks., mkd: ¼ S22 BT.

Douglas Co. Surveyors Office - Vernon "Ray" Tracy - Jack Heritage & V. Perron - Feb. 1968 - C.S. File 54/55 -18

Found "W" stump set for reference S.71½°E., 195.4 ft. - on top of 150 ft high bluff created by rock quarry it would be extremely difficult to re-establish the ¼ cor. from this reference.

Glenn S. Baughman - For: Umpqua Nat'l Forest, Glide Ranger District - C.S. File 55/112-10 & M37-42

Found - 2 stumps with Weyerhaeuser tags & nails:
 36" D.Fir stump S.28½°W., 90.9 ft.
 30" D.Fir stump bears N.81°W., 70.0 ft.

I was unable to set ¼ corner due to the point falling on the vertical face of a rock quarry.

Set - 1"x30" galv. IP with brass cap 10" in ground & then constructed a rock mound 16"x48" around pipe.

From this monument the true corner bears S.89°24'36"E., 125.99 ft.

T 24 S R 9 W
 W C
 S 15
 S 22
 1969
 OLS 536

From the iron pipe monument, I marked:
 4" Alder X & BTs which bears N.7°W., 55.9 ft.

Also set a 5/8"x30" iron rod 26" in the ground S.45°W., 107.0 ft.