TOWNSHIP 24 RANGE 09 POINT IDENTIFIER # 440500

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 10 & 15

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO retracement by Levi C. Walker, Deputy Surveyor, under special instructions, dated Aug. 23, 1905, independent of but in connection with his contract # 763, dated June 20, 1905 - (DCSO records Vol. 8 Page(s) 3442)

Set a fir post, 3 ft. long, 4" sq., 24" in the ground for ¼ sec. cor. marked ¼ S 10 on N, & 15 on S face; from which
A fir, 20" dia., bears N.50°E., 26½ lks., mkd: ¼ S10 BT.
A fir, 40" dia., bears S.16°E., 19 lks., mkd: ¼ S15 BT.

Douglas Co. Surveyors Office - Vernon "Ray" Tracy - Jack Heritage & V. Perron - Feb. 1968 - C.S. File 54/55

Found possible orig. BT stump cut below scribe & "W" referenced stump. Call on creek fits excellent.

Glenn S. Baughman - For: Umpqua Nat'l Forest, Glide Ranger District - C.S. File 55/112-6 & M37 - 42

Found - 2 Weyerhaeuser trees:
One is a 44" D.Fir stump with tag & a nail, also cruiser's mark. Tag gives bearing & distance as N.22½°W., 10.7 ft.
One is a 36" D.Fir stump with a tag & nail, giving bearing & dist. S.25°W., 40.5 ft.

Set - 1"x30" galv. iron pipe with brass cap, 26" in ground, & mkd: T24S R9W

¼
S 10
S 15
1969
OLS 536

From monument, I marked:
12" Maple,"¼ S10 BT" which bears N.57½°E., 100.4 ft.

Set - 5/8"x30" iron rod 26" in the ground which bears S.27°W., 47.0 ft.

Note - We do not have any record of a Weyerhaeuser report. DCSO (JC 7/28/2003)