

PRIMARY CORNER DESCRIPTION Closing Corner Secs. 14 & 23 (West)

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by W.H. Byars under contract #292, dated Aug 7, 1878 - (DCSO records Vol. 8 Page(s) 3403)

Set maple post 5 ft. long, 5" dia., 20" in ground for the corner to secs. 14, 15, 22, & 23, from which a:

- Fir, 36" dia., bears N.50°E., 40 lks.
- Fir, 16" dia., bears S.74°E., 45 lks.
- Fir, 30" dia., bears S.47°E., 18 lks.
- Fir, 12" dia., bears N.32°W., 40 lks.

GLO retracement by Levi C. Walker, Deputy Surveyor, under special instructions, dated Aug. 23, 1905, independent of but in connection with his contract # 763, dated June 20, 1905 - (DCSO records Vol. 8 Page(s) 3423)

The old post being in a poor state of preservation, I destroy it & at the same point, set a fir post, 3 ft. long, 4" sq. 24" in the ground, for cor. of secs. 14 & 23 only, marked.

- T 23 S S 14 on NE
- R 9 W S 23 on SE face with 3 notches on S., & 2 notches on E. edge.

Glenn S. Baughman - For: Umpqua Nat'l Forest, Glide Ranger District - C.S. File 55/112-7 & M37 - 42

Found - 22" D.Fir with open face & visible scribe with metal BT tags.

40" D.Fir with open face & visible scribe with metal BT tags.

From 22" D.Fir the corner bears N.47°W., 29.4 ft.

From 40" D.Fir the corner bears S.43°W., 25.2 ft.

Set - 1"x30" galv. iron pipe with brass cap, 26" in ground & mkd:

T 24 S	R 9 W
CC S 22	<u>S 14</u>
	S 23

1969
OLS 536

18" D.Fir T24S R9W S14BT which bears N.23°E. 42.7 ft

20" Hemlock T24S R9W S23BT bears S.29°E., 95.3 ft.

16" D.Fir T24S R9W S22BT which bears N.53°W. 79.6 ft

I placed BT tags on all BTs, facing the monument.