

PRIMARY CORNER DESCRIPTION Closing Corner Secs. 10 & 15 only, East

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO retracement by Levi C. Walker, Deputy Surveyor, under special instructions, dated Aug. 23, 1905, independent of but in connection with his contract # 763, dated June 20, 1905 - (DCSO records Vol. 8 Page(s) 3442)

Set a fir post 3 ft. long, 5" sq., 24" in the ground for CC of secs. 10 & 15, marked:
CC T 24 S R 9 W on W
S 10 on N and
S 15 on S face with 4 grooves on S face; from which
A fir, 40" dia. bears S.31°W. 38 lks. mkd: T24S R9W S15 BT
A fir, 40" dia., bears N.62½°W., 81 lks., mkd: T24S R9W S10 BT.

Douglas Co. Surveyors Office - Vernon "Ray" Tracy - J. Heritage & V. Perron - Feb/March 1968 - C.S. File 54/55-14

Found - Orig. 40" now 45" Fir, alive, S.31°W., 25.1 ft., shows good scar.
Orig. 40" now 46" Fir, alive, N.62½°W., 53.5 ft., open & find scribe marks.
Set brass cap at cor. mkd: County Surveyors T24S R9W S10 CC
S15

Rescribed BTs in bark below scars:
45" Fir S.31°W., 25.1 ft. mkd. T24S R9W S15 CC CS BT
46" Fir N.62½°W., 53.5 ft. mkd T24S R9W S10 CC CS BT
Note - This corner lies 316 ft. N of sec. cor. to secs. 11 & 14.

Tony Hostetter - March 2011 - C.S. File 65/72-24

Found - 3/4" iron pipe (1968 DCSO BC is gone), from which
45" fir stump, orig. BT, WEYCO tag, bears S.31°W., 25.1 ft.
46" fir stump, orig. BT, WEYCO tag, bears N.62½°W., 53.5 ft.
New BTs- 23" Fir WEYCO tag, bears S.45°E., 32.5 ft. to spike in root collar.
14" Fir WEYCO tag, bears S.18°W., 27.5 ft. to spike in root collar.
12" Fir WEYCO tag, bears N.55°W., 23.7 ft. to spike in root collar.