TOWNSHIP 24 RANGE 09 POINT IDENTIFIER # 600100

PRIMARY CORNER DESCRIPTION Sec. Cor. for 35 & 36, (South)

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by - William H. Byars, Deputy Surveyor, Under Contract No. 292, dated Aug. 7, 1878 - (DCSO records Vol. 8 Page(s) 3389)

Set Fir post 40" long, 5" dia., 20" in ground for the cor. to secs. 35 and 36 on S. bdy., from which a,

Fir 8" dia., bears N.50°E., 11 lks. dist.
Hemlock 10" dia., bears S.33°E., 25 lks. dist.
Fir 36" dia., bears S.21°W., 38 lks. dist.
Fir 30" dia., bears N.70°W., 26 lks. dist.

BLM Resurvey by James E. Jelly; Harvey E. Wofford; Wayne L. Rogers, Cadastral Surveyors, under Group #'s 926 and 958 - Surveyed Aug. 1977/April 1979 - (DCSO records Vol. 42 Page(s) 16438)

The cor. of secs. 35 and 36 only, determined from the remains of the original bearing trees:

A decayed Fir stump 10" dia., bears N.50°E., 11 lks. dist., no marks visible.
A Hemlock 16" dia., bears S.33°E., 25 lks. dist., with scribe marks S1 T25S R9W visible on partially healed double blaze.
A Fir 44" dia., bears S.21°W., 40 lks. dist., no marks visible. (Rec. 38 lks.)
A Fir 40" dia., bears N.70°W., 28 lks. dist. no marks visible. (Rec. 26 lks.)

At the corner point
Set an iron post, 28" long, 2 1/2" dia., 24" in the ground, with brass cap mkd: T 24 S R 9 W
S 35 S 36
1978

from which a new bearing tree

A Fir 35" dia., bears N.8°E., 43 lks. dist. mkd. T24S R9W S36 BT.