

TOWNSHIP 24 RANGE 09 POINT IDENTIFIER # 600300

PRIMARY CORNER DESCRIPTION Cor. Secs. 23, 24, 25, & 26

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by W.H. Byars under contract #292, dated Aug 7, 1878 - (DCSO records Vol. 8 Page(s) 3396)

-----

Set a fir post, 40" long, 5" dia., 18" in ground for cor. to secs. 25, 26, 24, & 23, from which

- Fir, 24" dia., bears N.20°E., 49 lks.
- Fir, 50" dia., bears S.10°E., 34 lks.
- Fir, 48" dia., bears S.35°W., 24 lks.
- Fir, 40" dia., bears N.64°W., 8 lks.

Tony Hostetter - For: Weyerhaeuser Co. Co. - March 2010 - C.S. File 65/69-8

-----

- Found - 3/4" iron pipe set by Weyerhaeuser. (Date Unknown)
- 22" Fir stump, Weyco Tag & "W" nail, bears N.02°E., 34.3 ft. to center.
  - 33" Fir stump, no marks, possible OBT, bears S.34°W., 17.6 ft. to center (GLO S.35°W. 24 lks.)
  - 36" Fir stump, no marks, possible OBT, bears N.64°W. 6.3 ft. to center (GLO N.64°W., 8 lks.)
  - 19" Fir stump, Weyco Tag, bears N.38°E., 19.5 ft. to center.
- New BTs- 18" Fir, Weyco Tag & spike, bears S.85°E., 55.2 ft. to spike.