

TOWNSHIP 24 RANGE 09 POINT IDENTIFIER # 600600

PRIMARY CORNER DESCRIPTION Cor. Secs. 1, 2, 11, & 12

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by W.H. Byars under contract #292, dated Aug 7, 1878 - (DCSO records Vol. 8 Page(s) 3399)

-----  
Set a hemlock post 40" long, 5" dia., 20" in ground, for the corner secs. 1, 12, 11, & 12 from which a  
    Fir, 30" dia., bears N.15°E., 12 lks.  
    Fir, 24" dia., bears S.60°E., 31 lks.  
    Fir, 18" dia., bears S.50°W., 8 lks.  
    Fir, 18" dia., bears N.68°W., 14 lks.

Tony Hostetter - For: Weyerhaeuser Co. - Sept. 2015 - C.S. File 65/89-66

-----  
Found - 3/4" iron pipe, set by Weyerhaeuser (date unknown)  
        20" fir stump, scribing visible, OBT, WEYCO tag and "W" nail, bears N.70°E., 33.7 ft. to face.  
        Decayed fir stump, scribing visible, bears S.75°W., 21.1 ft. to center.  
New BTs- 15" fir stump, 48" high, BT tag, bears S.52°E., 18.7 ft. to 6" spike, placed below tag.  
          17" fir stump, 60" high, BT tag, bears S.9°W., 11.3.4 ft. to 6" spike, placed below tag.  
          16" fir stump, 60" high, BT tag, bears N.25°W., 61.9 ft. to 6" spike, placed below tag.