TOWNSHIP 24 RANGE 09 POINT IDENTIFIER # 640100

PRIMARY CORNER DESCRIPTION So. 1/4 Cor. Sec. 36 only

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by - William H. Byars, Deputy Surveyor, Under Contract No. 292, dated Aug. 7, 1878 - (DCSO records Vol. 8 Page(s) 3389)

Set Cedar post 4 ft. long, 5" dia., 18" in ground for the ¼ sec. cor. on S. bdy. of Sec. 36, from which
A Fir 8" dia., bears S.23°W., 30 lks. dist.
A Cedar 10" dia., bears N.40°W., 21 lks. dist.

GLO survey by Morris Wygant, compassman for Zachariah M. Derrick, U.S. Deputy Surveyor, under Contract #779, dated Feb. 7, 1908 - (DCSO records Vol. 8 Page(s) 3388)

The ¼ sec. cor., on S. bdy. of sec. 36, which is a Cedar post, firmly set, mkd. and witnessed as described by the Surveyor General.

BLM Resurvey by James E. Jelly; Harvey E. Wofford; Wayne L. Rogers, Cadastral Surveyors, under Group #'s 926 and 958 - Surveyed Aug. 1977/April 1979 - (DCSO records Vol. 42 Page(s) 16437-38)

Point for the ¼ sec. cor. of sec. 36 only, determined by the method of irregular boundaries: there is no remaining evidence of the original corner.
Set an iron post, 28" long, 2 1/2" dia., 24" in the ground, with brass cap mkd: T 24 S R 9 W
1/4 S 36
1979
from which
A Hemlock 4" dia., bears N.59°E., 19 lks. dist. mkd. X BT.
A Hemlock 6" dia., bears N.71½°W., 16½ lks. dist. mkd. ¼ S36 BT.