

TOWNSHIP 24 RANGE 09 POINT IDENTIFIER # 640400

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 13 & 24

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by W.H. Byars under contract #292, dated Aug 7, 1878 - (DCSO records Vol. 8 Page(s) 3398)

-----  
Marked a fir 8" dia., for the ¼ sec. corner between secs. 13 & 24, from which a

Fir, 8" dia., bears S.45°E., 18 lks.

Fir, 10" dia., bears N.88°W., 19 lks.

-----  
Tony Hostetter - For: Weyerhaeuser Co. - March 2007 - C.S. 65/60-22

-----  
Found - 1/2" alum pipe (1965 Weyerhaeuser records indicate that the orig GLO corner tree & 2 BTs were found, the 1/2" alum. pipe & 2 new BTs were set at that time.) **Note DCSO has no rec. of this renewal**

From which:

10" Fir stump, OBT, no marks, bears; N.88°W., 11.7 ft (GLO 12.5 ft.) to center.

30" hemlock stump, WEYCO tag & "W" nail bears S.04°E., 30.0 ft to "W" nail.

28" fir stump, WEYCO tag & "W" nail, N.36°W. 18.0 ft to "W" nail.

New BTs- 16" fir, WEYCO tag & spike, bears: S.06°E., 27.7 ft to spike.

11" fir, WEYCO tag & spike, bears: S.78°W., 14.7 ft to spike

12" fir, WEYCO tag & spike, bears: n 54°w, 17.0 feet to spike.