

PRIMARY CORNER DESCRIPTION NE. Cor. Section 1, T25-9

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Charles L. Campbell, Deputy Surveyor, under Contract #747,, dated May 5,1902 - (DCSO records Vol. 10 Page(s) 3965)

Intersect S. bdy. of T24S R9W 23.54 chs. W. of the cor. of Tps. 24 and 25 S., Rs. 8 and 9 W., with is a post 4" sq., 1 ft. above ground mkd. and witnessed as described by the surveyor general. I destroy all markings on old cor. pertaining to Tps. 25 S., Rs. 8 and 9.

At point of intersection I set a Fir post 8 ins. sq. 3 ft. long 24 ins. in the ground for closing corner of Tps. 25 S. Rs. 8 & 9 W. Marked CC T25S on the S., R8W S6 on the E. and R9W S1 on the W. faces with 6 grooves on the S., E., & W., faces from which:

A Fir, 36" dia., bears S.30°E., 93 lks dist. mkd: T25S R8W S6 BT.

A Fir, 40" dia., bears S.61 3/4°W., 20 lks. dist. mkd: T25S R9W S1 BT.

GLO survey by Morris Wygant, compassman for Zachariah M. Derrick, U.S. Deputy Surveyor, under Contract #779, dated Feb. 7, 1908 - (DCSO records Vol. 8 Page(s) 3388 & Vol. 10 Pg. 3971)

(Page 3388)

Find no trace of the closing cor. to Tp. 25 S., Rs. 8 and 9 after diligent search.

(Page 3971)

At point of intersection, I set a Cedar post, 3 ft. long, 4" sq., 24" in the ground, for closing cor. of T25S Rs. 9 and 9 W., mkd. CC on S., T25S R8W S6 on E., T25S R9W S1 on W. faces; with 6 grooves on E., S. and W. faces; from which

A Cedar 60" dia., bears S.86°W., 11 lks. dist. mkd. T25S R9W S1 BT.

A Cedar 12" dia., bears S.60°E., 78 lks. dist. mkd. T25S R8W S6 BT.

Survey by Donald Peel - For: Weyerhaeuser Co. - May 1967 - C.S. File 55/30-4

Found - GLO survey record post, gone.

60" Cedar S.86°W., 11 lks., now Cedar snag, scribe visible.

12" Cedar S.60°E., 78 lks., now 16" Cedar already chopped open, scribe visible.

Set 4 ft. x 3/4" Pipe, 3 1/2 ft. in ground and square post.

(Cont. next page)

Alias_____	Description_____
Alias_____	Description_____
Alias_____	Description_____
Alias_____	Description_____

Re-referenced with "W" nails and plates only:
 30" Hemlock S.49°E., 65.6 ft.
 50" Fir S.28°W., 44.9 ft.

Douglas County Surveyors Office - Vernon "Ray" Tracy and crew
 Aug. 26, 1970 - C.S. File 54/72-49

Found - 1/2" steel Pipe and Weyerhaeuser BTs.
 Orig. 60" Cedar, down, S.86°W., 7.3 ft., scribe visible on decaying blaze.
 Orig. 12" now 16" Cedar, alive, S.60°E., 51.5 ft., opened, scribe visible. Rescribed "T25S R8W S6 CC CS BT".

Set Brass cap at cor. mkd. County Surveyors Office, 1970

	T	<u>25</u>	S
R9W		S 6	R8W

Reset steel tube alongside.
 New BT - 13" Hemlock S.15°W., 26.0 ft. mkd. CC CS BT.
 Corner lies on NE. slope in old growth timber.
 Also found 15x12x3" sandstone mkd. "CR 6", no record at this time.

BLM Resurvey by James E. Jelly; Harvey E. Wofford; Wayne L. Rogers, Cadastral Surveyors, under Group #'s 926 and 958 - Surveyed Aug. 1977/April 1979 - (DCSO records Vol. 42 Page(s) 16440)

True point for the closing cor. of T25S R8W.
 Set an Iron post 28" long, 2½" dia., 24" in the ground, with brass cap mkd. T 24 S R 9 W

	S	<u>36</u>
		T 25 S
		R 8 W
		S 6
C C		
		1979

from which
 A Hemlock 36" dia., bears S.51½°E., 99 lks. dist., mkd. T25S R8W S6 CC BT.
 A Cedar 35" dia., bears S.73°E., 265 lks. dist., mkd. T25S R8W S6 CC BT.

From this point, the closing cor. of T25S Rs. 8 and 9W., established by Wygant in 1911, bears N.0°12'E., 0.05 chs. dist., perpetuated and recorded by Tracy in 1970, determined at record brg. & dist. from the remains of an original bearing tree (Cont. next page)

TOWNSHIP 24 RANGE 09 POINT IDENTIFIER # 656100

PRIMARY CORNER DESCRIPTION NE Cor. Sec. 1, T25sr9w

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

A sawed Cedar stump 16" dia., bears S.60°E., 78 lks. dist. with illegible scribe marks visible on opened blaze and remarked by Tracy T25s R8W S6 CC CS BT on open blaze. and a bearing tree mkd. by Tracy

A Hemlock 18" dia., bears S.13°W., 40 lks. dist. with scribe marks CC CS BT visible on partially open blaze.