

PRIMARY CORNER DESCRIPTION Sec Cor for 25 & 36 only; T25-1W

Alias \_\_\_\_\_ Description \_\_\_\_\_  
 Alias \_\_\_\_\_ Description \_\_\_\_\_  
 Alias \_\_\_\_\_ Description \_\_\_\_\_  
 Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by Carl S. Nicklin, Deputy Surveyor, under joint contract #664 dated May 23, 1896 (DCSO records Vol. 8 Page(s) 3490)

-----

Set a Fir post 4 ft. long, 4" sq., 24" in the ground for cor. of secs. 25, 30, 31 and 36, marked T24S S30 on NE.; R1E S31 on SE.; S36 on SW.; and R1W S25 on NW.; faces, with 5 notches on N. and 1 notch on S. edges, from which

- A Fir 6" dia., bears N.51°E., 36 lks. dist. mkd. T25S R1E S30 BT.
- A Fir 6" dia., bears S.78°E., 20 lks. dist. mkd. T25S R1E S31 BT.
- A Fir 24" dia., bears S.14°W., 66 lks. dist. mkd. T25S R1W S36 BT.
- A Fir 36" dia., bears N.23°W., 51 lks. dist. mkd. T25S R1W S25 BT.

Cor. is on a hillside, sloping SW.

GLO Resurvey by Joseph A. Ganong and John G. Collins, Cadastral Surveyors, Under special instructions dated March 12, 1921 - (DCSO records Vol. 21 Page(s) 9110-11)

-----

The old cor. established for secs. 25, 30, 31 and 36, which is a badly decayed post, with marks illegible; from which

- A Fir 12" dia., bears N.51°E., 36 lks. dist. mkd. T25S R1E S30 BT. (Old BT)
- A Fir 12" dia., bears S.78°E., 20 lks. dist. mkd. T25S R1E S31 BT. (Old BT)
- A Fir 30" dia., bears S.14°W., 66 lks. dist., old BT, with marks burned out.
- A Pine 14" dia., bears S.70°W., 70 lks. dist. mkd. T25S R1W S36 BT. (New BT)
- A Fir 36" dia., bears N.23°W., 51 lks. dist. mkd. T25S R1W S25 BT. (old BT)

I now change this cor. to refer to secs. 25 and 36 only, and destroy the marks on the bearing trees in secs. 30 & 31.

In place of the decayed post

Set an Iron post 3 ft. long, 2" dia., 28" in the ground, for cor. of secs. 25 and 36 only, with brass cap marked

T25S	T25S
S 25	R1E
S 36	S30
R1W	
1927	

(Cont. Next Page)

PRIMARY CORNER DESCRIPTION Sec Cor for 25 & 36 only; T25-1W

Alias	Description
Alias	Description
Alias	Description
Alias	Description

Douglas County Surveyors Office - Vernon "Ray" Tracy and crew  
Oct. 1966 - C.S. File 52/30-27

-----  
Found - 1927 GLO brass cap, properly marked.  
Orig. 36" now 57" Pine, (not Fir) stump N.23°W.,  
33.7 ft., shows fair scar. We do not open.  
Orig. 30" now 30" Fir, 1 ft. high stump, S.14°W.,  
43.6 ft.  
14" now 20" Pine, now shattered stump, S.70°W., 46.2  
ft.  
Also find stumps of obliterated BTs to E. of line.  
New BTs- 14" D.Fir N.39°W., 42.0 ft. mkd. T25S R1W S36 CS BT  
12" Pine S.60°W., 108.3 ft. mkd. T25S R1W S36 CS BT.  
Corner lies approx. 85 ft. N. of closing cor. of 30 & 31,  
T25S R1E.

Kristian DeGroot - For: U.S. Forest Service - April/May 1992  
- C.S. File 63/138-20(A)

-----  
Found - 2" I.P. with 1927 GLO brass cap, properly mkd.,  
firmly set, projecting 20" above ground.  
1896 BT, a 42" Pine stump bears N.23°W., 33.7 ft.  
with a healed blaze.  
23" x 15 ft. tall Pine snag, bears S.60°W., 106.5  
ft. with a healed blaze. (Rec. 108.3 ft.) 1966  
23" D.Fir bears N.39°W., 42.9 ft. with a healed  
blaze. (Rec. 42 ft.) 1966  
New BT - 6" D.Fir bears S.25°W., 31.9 ft. scribed T25S R1W  
S36 BT.  
All BTs have a 6" red band painted around the tree and the  
blazed face painted red. USFS sign 54-3 BEARING TREE and  
sign 54-9 LAND SURVEYING MONUMENT, are nailed to all BTs.  
All new BTs have double blazed faces with a brass washer  
stamped "PLS 1941" nailed into the lower blaze.

Fd. BC, 2 BTs & Set 6' Steel post 2' S.85°W. - by D. Edwards  
8/2012 - M164-1