

TOWNSHIP 25 RANGE 01E POINT IDENTIFIER # 100300

PRIMARY CORNER DESCRIPTION C C for Secs. 19 & 30 only

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO Resurvey by Joseph A. Ganong and John G. Collins,
Cadastral Surveyors, Under special instructions dated March
12, 1921 - (DCSO records Vol. 21 Page(s) 9112-13)

Set an Iron post 3 ft. long, 2" dia., 28" in the ground, for
closing cor. of secs. 19 and 30, with brass cap marked

T25S		T25S	
R1W		S 19	CC
		S 30	
S25		R1E	
		1927	

from which

A Fir 16" dia., bears N.64°E., 128 lks. dist. mkd. T25S
R1E S19 CC BT.

A Fir 10" dia., bears S.62°E., 11 lks. dist. mkd. T25S R1E
S30 CC BT.

Douglas County Surveyors Office - Vernon "Ray" Tracy and crew
Oct. 1966 - C.S. File 52/30-31

Found - 1927 GLO brass cap, properly mkd. slightly bent over
16" now 24" Fir, N.64°E., 84.5 ft., now 5 ft. high
stump, shows good scar. Do not open.

10" now 14" Fir, S.62°E., 7.3 ft., alive, shows good
scar.

New BT - 20" W.Fir, N.45°E., 8.4 ft. mkd. T25S R1E S19 CC CS
BT.

Corner lies approx. 164 ft. South of the sec. cor. of 24 &
25, T25S R1W on moderate S. slope.