

PRIMARY CORNER DESCRIPTION C C for Secs. 18 & 19

Alias _____ Description _____
 Alias _____ Description _____
 Alias _____ Description _____
 Alias _____ Description _____

GLO Resurvey by Joseph A. Ganong and John G. Collins,
 Cadastral Surveyors, Under special instructions dated March
 12, 1921 - (DCSO records Vol. 21 Page(s) 9115)

 Set an iron post 3 ft. long, 2" dia., 28" in the ground for
 closing cor. of secs. 18 and 19, with brass cap marked

T25S	T25S	
R1W	S 18	CC
S 24	S 19	
	R1E	
	1927	

from which

A Fir 8" dia., bears N.61°E., 46 lks. dist. mkd. T25S R1E
 S18 CC BT.

A Fir 8" dia., bears S.40°E., 42 lks. dist. mkd. T25S R1E
 S19 CC BT.

 Douglas County Surveyors Office - Vernon "Ray" Tracy and crew
 Nov. 1966 - C.S. File 52/30

Found - 1927 GLO brass cap, properly marked.
 8" now 11" Fir snag, N.61°E., 30.4 ft., shows scar,
 we do not open.

8" now 10" Fir snag, S.40°E., 27.7 ft., shows scar,
 we do not open.

New BTs- 36" Cedar S.28°E., 7.4 ft. mkd. T25S R1E S19 CC CS
 BT.

13" D.Fir N.1°E., 31.6 ft. mkd. T25S R1E S18 CC CS
 BT.

Corner lies on SW. slope approx. 150 ft. S. of corner to
 secs. 13 and 24, T25S R1W.

 William Ruppert, LS #866 - For: U.S. Forest Service - Nov.
 1978 - C.S. File 58/176-12B

Found - 2" I.P. with 2½" 1927 GLO brass cap, properly mkd.
 30" Cedar snag, S.28°E., 6.4 ft.

9" D.Fir snag, S.40°E., 27.7 ft.

New BTs- 15" D.Fir, blazed and scribed "T25S R1E S18 CC BT"
 with brass washer mkd. "LS 866" attached, bears
 S.07°30'E., 31.3 ft.

10" D.Fir, blazed and scribed "T25S R1E S18 CC BT"
 with brass washer mkd. "LS 866" attached, bears
 N.77°00'E., 80.5 ft.

(Cont. Next Page)

TOWNSHIP 25 RANGE 01E POINT IDENTIFIER # 100400

PRIMARY CORNER DESCRIPTION C C for Secs. 18 and 19 only

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Gerald V. Nygren - For: U.S. Forest Service - June 11, 1987
-C.S. File 63/50-10

Found - 1927 GLO brass cap, properly marked.
30" Cedar snag, bears S.28°E., 6.4 ft.
9" D.Fir snag, down, bears S.40°E., 27.7 ft.
10" D.Fir, bears N.77°E., 80.5 ft.
15" D.Fir snag, bears S.07°30'E., 31.3 ft.
New BT - 6" D.Fir bears N.02°W., 21.5 ft. scribed "X" on
small upper blaze and "BT" on small lower blaze.
A ½" brass washer mkd. "RLS 1035" is nailed flush
to lower blaze.