

PRIMARY CORNER DESCRIPTION Sec Cor for 13 & 24 only; T25-1W

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Carl S. Nicklin, Deputy Surveyor, under joint contract #664 dated May 23, 1896 (DCSO records Vol. 8 Page(s) 3486)

Set a basalt stone 12x10x8 ins., 8" in the ground for cor. of secs. 13,18, 19 and 24, marked with 3 notches on N. and S. edges, from which

- A Fir 60" dia., bears N.32°E., 72 lks. dist. mkd. T25S R1E S18 BT.
- A Cedar 12" dia., bears S.31°E., 33 lks. dist. mkd. T25S R1E S19 BT.
- A Cedar 24" dia., bears S.19°W., 12 lks. dist. mkd. T25S R1W S24 BT.
- A Cedar 60" dia., bears N.74°W., 44 lks. dist. mkd. T25S R1W S13 BT.

GLO Resurvey by Joseph A. Ganong and John G. Collins, Cadastral Surveyors, Under special instructions dated March 12, 1921 - (DCSO records Vol. 21 Page(s) 9115-16)

The cor. established for secs. 13, 18, 19 and 24, which is a basalt stone, 6x10x8 ins. above ground, firmly set, marked with 3 notches on N. and S. edges; from which

- A Fir 60" dia., bears N.32°E., 72 lks. dist., old BT, the marks on which I now destroy.
- A Cedar 18" dia., bears S.31°E., 33 lks. dist., old BT, the marks on which I now destroy.
- A Fir, (not Cedar) 36" dia., bears S.19°W., 12 lks. dist. mkd. T25S R1W S13 BT.
- A Fir (not Cedar) 60" dia., bears N.74°W., 44 lks. dist., old BT, with marks grown over.

I now change this cor. to refer to secs. 13 and 24 only. Remark the stone S13 on NW.; and S24 on SW. face.

G. Robert Lecklider - For: U.S. Plywood Corp. - Aug. 1960 - M 19-46

Found Corner stone, from which
60" Fir, N.74°W., 29.0 ft.
42" Fir, S.19°W., 7.9 ft.
Set steel tube with survey cap.

Found OK, DCSO, Nov. 1966 - C.S. File 52/30-44A

Douglas Co. Surveyors Office - L.E. Monrean; P.L. Earle - Sept. 13, 1976 - C.S. File 59/24-10

(Cont. Next Page)

TOWNSHIP 25 RANGE 01E POINT IDENTIFIER # 100402

PRIMARY CORNER DESCRIPTION Sec Cor for 13 & 24 only; T25-1W

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Found - 48" (Rec. 60") Fir, now a stump, bears N.74°W., 29.0 ft. with blaze. I open and find scribing "T25S R1W S13 BT"

Stone, 16"x14"x7" (Rec. 6"x10"x8" above ground, orig. 12"x10"x8"), found 3 notches on opposite faces and S13 on another face. Rock has been dislodged by windfall bearing tree.

38" Fir (Rec. 36") is now a windfall. Tree has well healed blaze.

Steel tube with survey cap, dislodged by uprooted BT.

Set Brass cap at cor. mkd: County Surveyors Office
T 25 S

R			R
1	— S 13	S 18	1
W	S 24		W
	1976		

Set Corner stone on N. side of cap, set steel tube on S. side of cap.

New Accessories:

5/8" x 30" Iron rod with alum. cap in BT stump, bears N.75°W., 28.7 ft. Cap stamped "B.O. 1"

Spike in 40" Fir stump, bears S.50°W., 33.8 ft. stamped "B.O. 2"

Cedar post 2" sq. x 9 ft. Set post 2.4 ft. in the ground, bears North, 4.0 ft.