

PRIMARY CORNER DESCRIPTION W C (N) to Secs 12 & 13 only, T25-1W

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Carl S. Nicklin, Deputy Surveyor, under joint contract #664 dated May 23, 1896 (DCSO records Vol. 8 Page(s) 3484)

Brink of inaccessible canyon.

The Sec. cor. would fall within the canyon. Therefore, at this point, I Set a basalt stone 16x12x8 ins., 12" in the ground for witness cor. of secs. 7, 12, 13 and 18, marked W C on NE. face, with 2 notches on N. and 4 notches on S. edges, from which

A Fir 12" dia., bears S.74°E., 16 lks. dist. mkd. W C.
T25S R1E S18 BT.

A Fir 10" dia., bears N.10°W., 45 lks. dist. mkd. W C T25S
R1W S12 BT.

No other bearing trees available.

GLO Resurvey by Joseph A. Ganong and John G. Collins, Cadastral Surveyors, Under special instructions dated March 12, 1921 - (DCSO records Vol. 21 Page(s) 9118-19)

The witness cor. on the N. side of canyon, established for secs. 7, 12, 13 and 18, which is a basalt stone, 6x12x6 ins. above ground, firmly set, marked W C on NE. face, with 2 notches on N., and 4 notches on S. edges. I now change this cor. to refer to secs. 12 and 13, only. Re-Mark the stone W C S13 on SW.; and S12 on NW. face; from which

A Fir 16" dia., bears S.74°E., 16 lks. dist., old BT, the marks on which I now destroy.

A Fir 14" dia., bears S.38°W., 21 lks. dist., mkd. W C
T25S R1W S12 BT. (New BT)

A Fir 16" dia., bears N.10°W., 45 lks. dist., old BT, with marks grown over.

G. Robert Lecklider - For: U.S. Plywood Corp. - Aug. 1960 - M 19-46

Found - Corner stone.

16" Fir, N.10°W., 29.7 ft., down.

Set Steel tube with survey cap, mkd. "S12 B.O." on 20" x 20" rock face, N.16°W., 17.7 ft.

Douglas County Surveyors Office - Vernon "Ray" Tracy and crew Nov. 1966 - C.S. File 52/30-48

Found - Steel tube and alum. cap and rock face mkd. S12 BO, N.16°W., 17.7 ft.

Original rock with "WC" only.

(Cont. Next Page)

TOWNSHIP 25 RANGE 01E POINT IDENTIFIER # 100509

PRIMARY CORNER DESCRIPTION W.C. (N) to Secs. 12 & 13 only, T25-1W

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Set Brass cap 482.5 ft. No. of true corner (Note, dist. to true cor. not on brass cap mkd: County Surveyors Office
Wit. Cor. T25S

R1W $\frac{S}{S} \frac{12}{13}$ R1E

Set steel tube alongside brass cap.
There are no live trees West of line.
Marked new BTs to East:

9" Yew N.26°E., 39.0 ft. mkd. W.C. CS BT.
5" Yew N.85°E., 24.9 ft. mkd. W.C. CS BT.

This corner lies on top of vertical rock bluff 60 ft. high above N. fork of Hi Power Creek.

Kristian DeGroot - For: U.S. Forest Service - April/May 1992
C.S. File 63/138-20(B)

Found - 1966 DCSO brass cap on 1¼" I.P., firmly set, projecting 16" above the ground with a 2½" properly mkd. cap.
12" Yew bears N.26°E., 39.0 ft. with scribe marks "WC CS BT" visible.
8" Yew bears N.85°E., 24.9ft. with scribe marks "WC CS BT" visible.
1/2" steel tube with a 1" alum. cap is set flush with the South edge of the 1" BC/IP.

New BT - 6" D.Fir bears N.42°W., 31.1 ft. scribed "T25S R1W WC S12 BT.

All BTs have a 6" red band painted around the tree and the blazed face painted red. USFS sign 54-3 BEARING TREE and sign 54-9 LAND SURVEYING MONUMENT, are nailed to all BTs. All new BTs have double blazed faces with a brass washer stamped "PLS 1941" nailed into the lower blaze.