

PRIMARY CORNER DESCRIPTION E. 1/4 Cor. for Sec. 12 only; T25-1W

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Carl S. Nicklin, Deputy Surveyor, under joint contract #664 dated May 23, 1896 (DCSO records Vol. 8 Page(s) 3483)

Set a basalt stone 12x10x8 ins., 8" in ground for ¼ sec. cor. marked ¼ on W. face, from which

A Fir 30" dia., bears N.63°E., 18 lks. dist. mkd. ¼ S BT.

A Fir 12" dia., bears N.49°W., 53 lks. dist. mkd. ¼ S BT.
Cor. is on a steep hillside, sloping W.

GLO Resurvey by Joseph A. Ganong and John G. Collins, Cadastral Surveyors, Under special instructions dated March 12, 1921 - (DCSO records Vol. 21 Page(s) 9119-20)

The ¼ sec.cor. established for secs. 7 and 12, which is a basalt stone, 6x10x8 ins., firmly set, marked ¼ on W. face. I now change this cor. to refer to sec. 12 only.

Re-mark the stone ¼ S12 on W. face; from which

A Fir 36" dia., bears N.63°E., 18 lks. dist., old BT, the marks on which I now destroy.

A Fir 30" dia., bears S.21°W., 60 lks. dist. mkd. ¼ S12 BT. (New BT)

A Fir 16" dia., bears N.49°W., 53 lks. dist., old BT, with marks grown over.

G.R. Lecklider - For: U.S. Forest Service - Aug. 1960
M 19-46

Found - Corner stone and two trees:

24" Fir N.49°W., 35.0 ft.

36" Fir S.21°W., 39.6 ft.

Set steel tube with survey cap.

Douglas County Surveyors Office - Vernon "Ray" Tracy and crew
Oct/Nov. 1966 - C.S. File 52/30

Found - Stone, mkd. "¼ S12" on West face.

Orig. 16" now 21" Fir stump, N.47°W., 35.0 ft., shows good scar. We do not open.

30" now 36" Fir stump, S.21°W., 44.2 ft. (not 39.6 ft.), open and find reverse scribing.

Orig. 36" now 42" Fir, N.63°E., 11.9 ft., shows scar, recorded as marks obliterated. Alive, use as reference only.

Set Brass cap at cor. mkd: County Surveyors Office

T25S R1W ¼ S12 | R1E

1966

(Cont. Next Page)

TOWNSHIP 25 RANGE 01E POINT IDENTIFIER # 100542

PRIMARY CORNER DESCRIPTION E. 1/4 Cor. for Sec. 12 only; T25-1W

| | |
|-------------|-------------------|
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |

New BTs- 23" D.Fir N.78°E., 24.9 ft. mkd. ¼ S CS BT.
No trees available to West of line due to logging.
1/2" steel pin with 1" alum. cap mkd. "Prop. Cor."

Kristian DeGroot, LS #1941 - For: U.S. Forest Service -
April/May 1992 - C.S. File 63/138-20(E)

Found - 1¼" I.P. with 1966 DCSO brass cap, firmly set,
projecting 16" above the ground.
43" Fir bears N.60°E., 10.5 ft. with a healed blaze.
(Rec. N.63°E., 18 lks.) 1896 BT.
21" Fir stump bears N.47°W., 35.0 ft. with a healed
blaze. (Rec. N.49°W.) 1896 BT
36" Fir stump bears S.21°W., 42.4 ft. with scribe
marks "12" visible. (Rec. 60 lks.) 1927
20" D.Fir bears N.78°E., 24.9 ft. with a healed
blaze. 1927 BT.
1/2" steel tube with a 1" survey cap, bears S.58°E.,
1.6 ft.
New BT - 9" D.Fir bears S.30°W., 59.9 ft. scribed "¼ S12 BT."