

PRIMARY CORNER DESCRIPTION C C for Secs. 6 & 7 only

Alias \_\_\_\_\_ Description \_\_\_\_\_  
 Alias \_\_\_\_\_ Description \_\_\_\_\_  
 Alias \_\_\_\_\_ Description \_\_\_\_\_  
 Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO Resurvey by Joseph A. Ganong and John G. Collins, Cadastral Surveyors, Under special instructions dated March 12, 1921 - (DCSO records Vol. 21 Page(s) 9120)

-----  
 Set an Iron post 3 ft. long, 2" dia., 28" in the ground, for closing cor. of secs. 6 and 7, with brass cap marked:

T25S	T25S	
R1W	S $\frac{6}{7}$	-- CC
S12	R1E	
	1927	

from which

A Fir 18" dia., bears N.61°E., 10 lks. dist. mkd. T25S R1E S6 CC BT.

A Fir 24" dia., bears S.17°E., 75 lks. dist. mkd. T25S R1E S7 CC BT.

Glenn Baughman - For: U.S. Forest Service - Sept. 1980 - C.S. File 58/229-36

-----  
 Found - 1927 GLO brass cap, properly mkd. on a 2" Iron post, firmly set, 10" above ground.

21" D.Fir, orig., with healed blaze, bears N.61°E., 6.6 ft.

24" wind fallen D.Fir, orig., with healed blaze, bears S.17°E., 49.6 ft.

New BT - 17" D.Fir bears S.7°E., 42.7 ft. mkd. "T25S R1E S7 CC BT" on a double blaze with a brass washer stamped "LS 536" nailed into lower blaze.

Kristian DeGroot, LS #1941 - For: U.S. Forest Service - May 1992 - C.S. File 63/138-20(C)

-----  
 Found - 2" I.P. with 1927 BLM brass cap, firmly set, projecting 9" above ground, Cap properly marked.

24" D.Fir stump, bears N.61°E., 6.6 ft. with a healed blaze.

24" windfallen D.Fir, bears S.17°E., 49.5 ft. with a healed blaze.

14" Grand Fir, bears S.7°E., 42.7 ft. with a healed blaze.

New BT - 8" Grand Fir bears N.44°E., 56.6 ft. scribed "T25S R1E S6 BT."

All BTs have a 6" red band painted around the tree and the blazed face painted red. U.S.F.S. sign 54-3, BEARING TREE, and sign 54-9 LAND SURVEYING MONUMENT, are nailed to all BTs.

(Cont. Next Page)

TOWNSHIP 25 RANGE 01E POINT IDENTIFIER # 100600

PRIMARY CORNER DESCRIPTION C C for Secs. 6 & 7 only

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

All new BTs have double blazed with a brass washer stamped "PLS 1941" nailed into the lower blaze. Brgs. are taken to the center of the tree at the root crown, and distances are measured to the root crown at the side and center of the tree. Brg. & dist. were measured with a staff compass (dec. 20°) and steel tape.

Douglas McMahan - For: Seneca Jones Tmbr Co. 9/2020 - M177-49

-----  
Found - 1927 GLO 2½" brass cap on an iron pipe  
BT - 32" W.Fir, bears S.17°E., 49.5 ft. "healed face"  
Note - From M177-49 the East sec corner to secs 1 & 12  
only, T25-1W bears N.3°08'18"W., 152.12' -(DCSO JC)