

TOWNSHIP 25 RANGE 01E POINT IDENTIFIER # 138700

PRIMARY CORNER DESCRIPTION 1/4 Cor. Sec. 31 only, T24-1E

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Alonso Gesner, Deputy Surveyor, under contract No. 659, dated May 21, 1896 - (DCSO records Vol. 21 Pg 9099)

Set basalt stone 14x8x5", 12" in the ground, on steep hillside, sloping NE, for ¼ sec. cor. mkd. ¼ on N face, from which

- A silver fir, 18" dia., bears S.10°W., 19 lks. mkd: ¼ S BT
- A silver fir, 10" dia., bears N.30°W., 10 lks. mkd: ¼ S BT

GLO survey by Joseph A Ganong & John G Collins, US Cadastral Engineers under instructions dated March 12, 1921, surveyed May 1927/June 1928 - (DCSO Records Vol. 21 Page(s) 9136)

The ¼ sec. cor. established for secs. 6 & 31, which is a basalt stone, 6x8x5" above ground, firmly set, marked ¼ on N face.

I now change this cor. to refer to sec. 31 only.

Re-mark the stone ¼ S31 on N face; from which

- A fir, 10" dia., bears N.15°E., 32 lks., mkd: ¼ S31 BT.
(New BT)
- A fir, 20" dia., bears S.10°W., 19 lks., old BT the marks on which I now destroy.
- A fir, 14" dia., bears N.30°W., 10 lks., old BT with marks grown over.