

PRIMARY CORNER DESCRIPTION South Cor. Secs. 31 & 32; T24-1E

Alias	Description

GLO survey by Alonso Gesner, Deputy Surveyor, under contract No. 659, dated May 21, 1896 - (DCSO records Vol. 21 Page(s) 9099-9100)

Set basalt stone, 18x6", 12" in the ground, on steep hillside sloping West for cor. to Secs. 31, 32, 5 & 6 marked with 1 notch on the W & 5 notches on the E sides, from which
A fir, 5" dia., bears N.37°30'E., 28 lks., mkd: T24S R1E S32 BT.
A fir, 10" dia., bears S.85°45'E., 30 lks., mkd: T25S R1E S5 BT.
A fir, 8" dia., bears S.60°45'W., 15 lks., mkd: T25S R1E S6 BT.
A fir, 30" dia., bears N.44°W., 65 lks., mkd: T24S R1E S31 BT.

GLO survey by Joseph A Ganong & John G Collins, US Cadastral Engineers under instructions dated March 12, 1921, surveyed May 1927/June 1928 - (DCSO Records Vol. 21 Page(s) 9134-5)

The cor. established for secs. 5, 6, 31, & 32, which is a basalt stone, 6x16x8" above ground, firmly set, marked with 1 notch on W and 5 notches on E edges;
I now change this cor. to refer to secs. 31 & 32 only.
Re-mark the stone S32 on NE and S31 on NW face; from which
A fir, 10" dia., bears N.37½°E., 28 lks., old BT with marks grown over.
A fir, 14" dia., bears S.85¾°E., 30 lks., old BT the marks on which I now destroy.
A fir, 12" dia., bears S.60¾°W., 15 lks., old BT the marks on which I now destroy.
A fir, 30" dia., bears N.44°W., 65 lks., old BT with marks grown over.