

TOWNSHIP 25 RANGE 01E POINT IDENTIFIER # 200200

PRIMARY CORNER DESCRIPTION Cor. Secs. 29, 30, 31, & 32

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Joseph A Ganong & John G Collins, US Cadastral Engineers under instructions dated March 12, 1921, surveyed May 1927/June 1928 - (DCSO Records Vol. 22 Page(s) 9206-7)

Set an iron post, 3 ft. long, 2" dia., 27" in the ground, for cor. of secs. 29, 30, 31, & 32, with brass cap mkd

T25S R1E
S 30 | S 29
S 31 | S 32
1927

from which

- A pine, 56" dia., bears N.34°E., 115 lks., mkd: T25S R1E S29 BT.
- A fir, 18" dia., bears S.79°E., 97 lks., mkd: T25S R1E S32 BT.
- A fir, 28" dia., bears S.18°W., 46 lks., mkd: T25S R1E S31 BT.
- A fir, 18" dia., bears N.51°W., 158 lks., mkd: T25S R1E S30 BT.

Fd. 1927 BC & all 4 BTs alive & in good cond. DCSO VRT - 3/24/1967 - C.S. File 52/30-76A