

TOWNSHIP 25 RANGE 01E POINT IDENTIFIER # 200300

PRIMARY CORNER DESCRIPTION Cor. Secs. 19, 20, 29, & 30

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Joseph A Ganong & John G Collins, US Cadastral Engineers under instructions dated March 12, 1921, surveyed May 1927/June 1928 - (DCSO Records Vol. 22 Page(s) 9210)

Set an iron post, 3 ft. long, 2" dia., 27" in the ground, for cor. of secs. 19, 20, 29, & 30, with brass cap mkd

T25S R1E
S 19 | S 20
S 30 | S 29
1927

from which

- A fir, 10" dia., bears N.76½°E., 61 lks., mkd: T25S R1E S20 BT.
- A fir, 10" dia., bears S.26°E., 78 lks., mkd: T25S R1E S29 BT.
- A fir, 8" dia., bears S.35½°W., 30 lks., mkd: T25S R1E S30 BT.
- A fir, 8" dia., bears N.21°W., 81 lks., mkd: T25S R1E S19 BT.

Fd. 1927 BC & BTs, DCSO - April 4, 1967 - C.S. File 52/30-77A