

TOWNSHIP 25 RANGE 01E POINT IDENTIFIER # 200500

PRIMARY CORNER DESCRIPTION Cor. Secs. 7, 8, 17 & 18

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by Joseph A Ganong & John G Collins, US Cadastral Engineers under instructions dated March 12, 1921, surveyed May 1927/June 1928 - (DCSO Records Vol. 22 Page(s) 9217)

-----  
Set an iron post, 3 ft. long, 2" dia., 27" in the ground, for cor. of secs. 7, 8, 17, & 18, with brass cap mkd

T25S R1E  
S 7 | S 8  
S 18 | S 17  
1927

from which

- A fir, 24" dia., bears N.74°E., 38 lks., mkd: T25S R1E S8  
BT.
- A fir, 13" dia., bears S.24°E., 42 lks., mkd: T25S R1E S17  
BT.
- A fir, 48" dia., bears S.82°W., 54 lks., mkd: T25S R1E S18  
BT.
- A fir, 10" dia., bears N.11°W., 12 lks., mkd: T25S R1E S7  
BT.