

TOWNSHIP 25 RANGE 01E POINT IDENTIFIER # 238700

PRIMARY CORNER DESCRIPTION S 1/4 Cor. Sec. 32 only

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Alonso Gesner, Deputy Surveyor, under contract No. 659, dated May 21, 1896 - (DCSO records Vol. 21 Pg 9100)

Set basalt stone 16x14x4", 12" in the ground for ¼ sec. cor. mkd. ¼ on N face, from which

A Silver Fir, 7" dia., bears S.62°E., 18 lks., mkd: ¼ S BT.

A Silver Fir, 26" dia., bears N.42°W., 15 lks., mkd: ¼ S BT.

GLO survey by Joseph A Ganong & John G Collins, US Cadastral Engineers under instructions dated March 12, 1921, surveyed May 1927/June 1928 - (DCSO Records Vol. 21 Page(s) 9133-4)

The ¼ sec. cor. established for secs. 5 & 32, which is a basalt stone, 6x12x4" above ground, firmly set, marked ¼ on N face.

I now change this cor. to refer to sec. 32 only.

Re-mark the stone ¼ S 32 on N face; from which

A fir, 14" dia., bears N.80°E., 22 lks., mkd: ¼ S32 BT.
(New BT)

A fir, 30" dia., bears N.42°W., 15 lks. old BT with marks grown over.

The old BT in sec. 5 is dead.