

TOWNSHIP 25 RANGE 01E POINT IDENTIFIER # 278700

PRIMARY CORNER DESCRIPTION S Cor. Secs. 32 & 33 only, T24-1E

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Alonso Gesner, Deputy Surveyor, under contract No. 659, dated May 21, 1896 - (DCSO records Vol. 21 Pg 9101)

-----  
Set basalt stone 18x12x8" 16" in the ground on hillside, sloping gradually to the South, for cor. to secs. 32, 33, 4 & 5, marked with 2 notches on the W and 4 notches on the E sides, from which

- A hemlock, 4" dia., bears N.27°E., 18 lks., mkd: T24S R1E S33 BT.
- A Silver Fir, 14" dia., bears S.81°E., 43 lks., mkd: T25S R1E S4 BT.
- A R.Fir, 30" dia., bears S.57°W., 23 lks., mkd: T25S R1E S5 BT.
- A Silver Fir, 14" dia., bears N.34°W., 34 lks., mkd: T24S R1E S32 BT.

GLO survey by Joseph A Ganong & John G Collins, US Cadastral Engineers under instructions dated March 12, 1921, surveyed May 1927/June 1928 - (DCSO Records Vol. 21 Page(s) 9132-3)

-----  
The cor. established for secs. 4, 5, 32 and 33, which is a basalt stone, 6x12x8" above ground, firmly set, marked with 2 notches on W and 4 notches on E edges.

I now change this cor. to refer to secs 32 and 33 only.  
Re-mark the stone

S33 on NE and  
S32 on NW face;

from which

- A hemlock, 10" dia., bears N.27°E., 18 lks., old BT with marks grown over.
- A fir, 16" dia., bears S.81°E., 43 lks., old BT the marks on which I now destroy.
- A fir, 30" dia., bears S.57°W., 23 lks. old BT the marks on which I now destroy.
- A fir, 16" dia., bears N.34°W., 34 lks., old BT with marks grown over.