

TOWNSHIP 25 RANGE 01E POINT IDENTIFIER # 300200

PRIMARY CORNER DESCRIPTION Cor. Secs. 28, 29, 32, & 33

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Joseph A Ganong & John G Collins, US Cadastral Engineers under instructions dated March 12, 1921, surveyed May 1927/June 1928 - (DCSO Records Vol. 22 Page(s) 9193)

Set an iron post, 3 ft. long, 2" dia., 27" in the ground, for cor. of secs. 28, 29, 32, & 33, with brass cap mkd

T25S R1E
S 29 | S 28
S 32 | S 33
1927

from which

- A fir, 8" dia., bears N.56°E., 26 lks mkd: T25S R1E S28 BT
- A fir, 8" dia., bears S.33°E., 31 lks mkd: T25S R1E S33 BT
- A fir, 8" dia. bears S.69½°W., 22 lks mkd: T25S R1E S32 BT
- A fir, 8" dia., bears N.39°W., 20 lks mkd: T25S R1E S29 BT

Douglas Co. Surveyors Office - Randall W. Smith - Stephen J. Flause - 1/14/1986 - C.S. File 62/31-8

Found - 1927 GLO brass cap/iron pipe protruding 18" above ground, leaning 7" southeast of plumb.

8" now indeterminate dia. rotted 6" high D.fir stump. No scribing found bears N.56°E., 17.16 ft. (agrees with record)

8" now 18" dia. D.fir with a fully healed single blaze bears S.34½°E., 13.5 ft. (Rec. S.33°E., 20.46 ft. dist. is probably to NW BT.)

8" now 17" dia. D.fir with a fully healed single blaze bears N.39°W., 19.6 ft. (Rec. N.39°W., 13.20 ft. dist. is probably to SE BT)

8" now 15" dia. D.fir with a fully healed single blaze bears S.67½°W., 13.8 ft. (Rec. S.69½°W., 14.52 ft.)

Set - USGLO brass cap/iron pipe returned to plumb position and a 2 ft. dia. mound of stone 14" high placed around I.P. BC/I.P. protrudes 4" above mound of stone.

Plumb position of BC/IP re-monumented as corner location. The NW and SE BTs distances appear to be interchanged; if that problem is corrected the bearings and distances to orig. BTs agree closely with record information.

New BT - 14" dia. D.fir double blazed scribed "T25S R1E S28 CS BT" bears N.64½°E., 51.3 ft.

Corner lies on level ground.