

TOWNSHIP 25 RANGE 01E POINT IDENTIFIER # 300600

PRIMARY CORNER DESCRIPTION Cor. Secs. 4, 5, 8, & 9

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Joseph A Ganong & John G Collins, US Cadastral Engineers under instructions dated March 12, 1921, surveyed May 1927/June 1928 - (DCSO Records Vol. 22 Page(s) 9202-3)

N.0°03'W., bet. secs. 8 & 9
80.00 chs

The point for the sec. cor. falls at the S. edge of a creek, 8 lks. wide, course E.

80.58 chs

Set an iron post, 3 ft. long, 2" dia., 27" in the ground, for cor. of secs. 4, 5, 8, & 9, with brass cap mkd

T25S R1E

S 5 | S 4

S 8 | S 9

WC

1927

from which

A cedar, 10" dia., bears N.21°E., 55 lks., mkd: WC T25S R1E S4 BT.

A fir, 12" dia., bears S.37°E., 92 lks., mkd: WC T25S R1E S9 BT.

A fir, 14" dia., bears S.24°W., 96 lks., mkd: WC T25S R1E S8 BT.

A fir, 30" dia., bears N.81°W., 16 lks., mkd: WC T25S R1E S5 BT.