

TOWNSHIP 25 RANGE 01E POINT IDENTIFIER # 338700

PRIMARY CORNER DESCRIPTION South 1/4 Cor. Sec. 33 only, T24-1E

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Alonso Gesner, Deputy Surveyor, under contract No. 659, dated May 21, 1896 - (DCSO records Vol. 21 Pg 9101)

Set sandstone 14x12x3", 10" in the ground on steep, rocky hillside, sloping NE, for ¼ sec. cor. mkd. ¼ on N face, from which

- A fir, 10" dia., bears S.28°W., 28 lks., mkd: ¼ S BT.
- A fir, 10" dia., bears N.13°E., 42 lks., mkd: ¼ S BT.

GLO survey by Joseph A Ganong & John G Collins, US Cadastral Engineers under instructions dated March 12, 1921, surveyed May 1927/June 1928 - (DCSO Records Vol. 21 Page(s) 9131-2)

The sec. cor. established for secs. 4 & 33, which is a sandstone, 6x12x4" above ground, firmly set, marked ¼ on N face.

I now change this cor. to refer to sec. 33 only.

Re-mark the stone 5 33 on N. face; from which.

- A fir, 14" dia., bears N.13°E., 42 lks. old BT with marks grown over.
- A fir, 14" dia., bears S.28°W., 28 lks., old BT the marks on which I now destroy.
- A fir, 10" dia., bears N.42½°W., 32 lks., mkd ¼ S33 BT (New B.T.)