

PRIMARY CORNER DESCRIPTION South Cor. Secs. 33 & 34 only; T24-1E

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Alonso Gesner, Deputy Surveyor, under contract No. 659, dated May 21, 1896 - (DCSO records Vol. 21 Pg 9102)

Set sandstone 14x12x6" 10" in the ground, in thicket of undergrowth and on steep hillside, sloping SE for cor. to Secs. 33, 34, 3, & 4 marked with 3 notches on the E & W edges, from which

- A fir, 6" dia., bears N.8°E., 25 lks., mkd: T24S R1E S34 BT.
- A fir, 8" dia., bears S.31°30'E., 54 lks., mkd: T25S R1E S3 BT.
- A fir, 12" dia., bears S.8°W., 20 lks., mkd: T25S R1E S4 BT.
- A madrone, 8" dia., bears N.41°30'W., lks., mkd: T24S R1E S33 BT.

GLO survey by Joseph A Ganong & John G Collins, US Cadastral Engineers under instructions dated March 12, 1921, surveyed May 1927/June 1928 - (DCSO Records Vol. 21 Page(s) 9130)

The cor. established for secs. 3, 4, 33 and 34, which is a sandstone, 6x12x6" above ground, firmly set, marked with 3 notches on E. and W. edges.

I now change this cor. to refer to seas. 33 and 34 only.
Re-mark the stone,

- S34 on NE., and
- S33 on NW. face; from which
- A fir, 12" dia., bears N.14°E., 23 lks., old BT with marks grown over.
- A fir, 12" dia., bears S.31½°E., 54 lks., old BT the marks on which I now destroy.
- A fir, 16" dia., bears S.8°W., 20 lks., old BT the marks on which I now destroy.
- A madrona, 14" dia., bears N.41½°W., 45 lks., old BT with marks grown over.

Douglas Co. Surveyors Office - Larry E. Monrean, Deputy - J.R. Lundeen - R.W. Smith - S.J. Flause - Sept. 21, 1984 - C.S. File 62/21-7

Found - Orig. stone monument searched for and NOT FOUND.
Orig. 12" now 19" fir bears N.14°E., 15.2 ft. We opened a portion of well healed blaze and found a scribed "4" at the proper growth ring count.
12" now 29" fir bears S.31½°E., 30.8 ft. (Rec. 35.6 ft.) Fd fragmentary scribe marks in the previously opened and obliterated blaze.

TOWNSHIP 25 RANGE 01E POINT IDENTIFIER # 378700

PRIMARY CORNER DESCRIPTION South Cor. Secs. 33 & 34 only; T24-1E

Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____

A 16" now 28" fir bears S.11½°W., 13.2 ft. (Rec. S.8°W.) Tree has well healed overlapping blazes. The original 8" madrone BT NOT FOUND.

CC 3 and Sec. 4 of T25S bears N.89¼°E., 86.8 ft. (Rec. N.89¼°E., 84.5 ft.)

Set - At the location determined by holding the record bearing and distance (N.14°E., 15.2 ft.) to the NE BT & corroborated with the noted measurements, We chisel a 2" + into the bedrock. 6" below ground surface. Over this point, We set a 1"x30" iron pipe with brass cap in mound of stone and earth. Cap marked "Douglas Co. Surveyor" T24S R1E S33 S34/S4 T25S" Corner lies on steep SSE slope.

New BTs- 11" dia., pistol butt D.Fir bears N.67°E., 19.2 ft. to center of root crown is double blazed and scribed "T24S R1E S34 CS BT"

11" dia. maple scribed "T24S R1E S33 CSBT" on a double blaze bears N.67½°W., 48.2 ft. to center of root crown.

Not of record -

A tagged 28" fir snag bears N.50°W., 34.5 ft.

A tagged 32" Fir bears S.68°E., 43.4 ft.

Note - Compass decl. 18½°E.