

TOWNSHIP 25 RANGE 01E POINT IDENTIFIER # 400400

PRIMARY CORNER DESCRIPTION Cor. Secs. 15, 16, 21, & 22

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Joseph A Ganong & John G Collins, US Cadastral Engineers under instructions dated March 12, 1921, surveyed May 1927/June 1928 - (DCSO Records Vol. 22 Page(s) 9186)

-----  
A Hemlock 12, 15, 16, 21, & 22, I mark  
    T25S S15 on NE  
    R1E S22 on SE  
    S21 on SW and  
    S 16 ON NW side

from which

- A hemlock, 8" dia., bears N.32°E., 18 lks., mkd: T25S R1E S15 BT.
- A fir, 20" dia., bears S.18°E., 43 lks., mkd: T25S R1E S22 BT.
- A hemlock, 14" dia., bears S.63°W., 29 lks., mkd: T25S R1E S21 BT.
- A hemlock, 8" dia., bears N.23½°W., 56 lks., mkd: T25S R1E S16 BT.

D. G. Heuschkel - For: Forrest Alberti - Nov. 24, 1958 - C.S. File 42/405

-----  
This corner was a 12" Hemlock which had been tied to a cutting unit boundary by Forest Service surveyors. Although marked to be saved, the tree was destroyed during logging. The Forest Service admin. present then placed a temporary metal pipe in the stump hole. The logger, Mr. Alberti confirmed the location. Blazes still exist intercepting the stump hole from all directions.

A Wild Theodolite was used in reestablishing the corner.

- A Pipe 2" in dia. & 42" long marks the corner. From it
- A Pipe 2" by 25" bears N.32°7'W., a distance of 13'7"
- A Pipe 1½" by 28" bears N.57°32'E., a distance of 13'1"
- A Pipe 1½" by 24" bears S.66°6'E., a distance of 14'2";
- A Pipe 2" by 28" bears S.58°16'W., a distance of 18'5".