

TOWNSHIP 25 RANGE 01E POINT IDENTIFIER # 400700

PRIMARY CORNER DESCRIPTION Closing Cor. Secs. 3 & 4 only

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Joseph A Ganong & John G Collins, US Cadastral Engineers under instructions dated March 12, 1921, surveyed May 1927/June 1928 - (DCSO Records Vol. 21 Page(s) 9130)

Set an iron post, 3 ft. long, 2" dia., 27" in the ground, for closing cor. of secs. 3 & 4, with brass cap mkd

T24S R1E
S 34

S 4 | S 3
T25S | SR1E
C C
1928

from which

- A fir, 12" dia., bears S.60°E., 23 lks., mkd: T25S R1E S3
C C BT.
- A fir, 14" dia., bears S.10°W., 39 lks., mkd: T25S R1E S4
C C BT.

Douglas Co. Surveyors Office - Larry E. Monrean, Deputy - J.R. Lundeen - R.W. Smith - S.J. Flause - Sept. 21, 1984 - C.S. File 62/21-8

Found - 1928 GLO 2½" cap on a 2" iron pipe protruding 21" above ground, properly marked.
12" now 18" fir bears S.60°E., 14.2 ft. to center of root crown 15.2 ft. to center of tree (Rec. S.60°E., 15.2 ft.) Has well healed single blaze.
A 14" now 20" fir with well healed single blaze bears S.10°W., 25.7 ft. to center of root crown.
New BTs- 28" dia. D.Fir double blazed and scribed "S 34 CS BT" bears N.21½°E., 29.7 ft.
29" dia. D.Fir double blazed and scribed "T25S R1E CC S3 CS BT" bears S.3½°E., 28.5 ft.
New BTs measured to center of root crown.
Note - Compass decl. 18½°E