

TOWNSHIP 25 RANGE 01E POINT IDENTIFIER # 438700

PRIMARY CORNER DESCRIPTION S 1/4 Cor. Sec. 34 only, T24-1E

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Alonso Gesner, Deputy Surveyor, under contract No. 659, dated May 21, 1896 - (DCSO records Vol. 21 Pg 9103)

Set sandstone, 13x8x6", 8" in the ground, on steep rocky hillside, sloping SW for ¼ sec. cor. marked ¼ on N side, from which

A fir, 8" dia., bears North, 12 lks., mkd: ¼ S BT.

A fir, 6" dia., bears S.30°E., 16 lks., mkd: ¼ S BT.

GLO survey by Joseph A Ganong & John G Collins, US Cadastral Engineers under instructions dated March 12, 1921, surveyed May 1927/June 1928 - (DCSO Records Vol. 21 Page(s) 9129)

The ¼ sec. cor. established for secs. 3 and 34, which is a sandstone, 6x8x6" above ground, firmly set, mkd ¼ on N face. I now change this oar, to refer to sec. 34 only.

Re-mark the stone S 34 on N. face; from which.

A fir, 16" dia., bears North, 12 lks., old B.T. with marks grown over.

A cedar, 6" dia., bears N.9½°E., 24 lks., marked ¼ S34 BT. (New B.T.)

A fir, 12" dia., bears S.30°E., 26 (not 16) lks., old BT, the marks on which I now destroy,