

TOWNSHIP 25 RANGE 01E POINT IDENTIFIER # 440200

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 27 & 34

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Joseph A Ganong & John G Collins, US Cadastral Engineers under instructions dated March 12, 1921, surveyed May 1927/June 1928 - (DCSO Records Vol. 22 Page(s) 9181)

Set an iron post, 3 ft. long, 1" dia., 27" in the ground, for 1/4 sec. cor., with brass cap marked

1/4 S 27
S 34
1927

from which

A cedar, 24" dia., bears S.25°W., 23 lks., mkd: 1/4 S34 BT.
A fir, 24" dia., bears N.31°W., 56 lks., mkd: 1/4 S27 BT.

Kristian DeGroot, PLS 1941 - For: USFS - Crew: Les Fanning, Matt Dixon, & Aaron Fanning - March 1998 - C.S. File 65/20-7

Found - 1" OD iron pipe, firmly set, projecting 10" above the ground with a 2 1/2" brass cap properly stamped.

30" high stumped D.Fir bears N.31°W., 37.0 ft w/healed face. 1927

24" Cedar root crown bears S.25°W., 15.2 ft.

Set - I build a stone mound, 48" dia., base to top of monument.

6" D.Fir bears N.21°E., 12.5 ft. scribed "1/4 S27 BT"

6" D.Fir bears S.20°E., 12.5 ft. scribed "1/4 S34 BT"

I nail a brass washer stamped "PLS 1941" into the lower blaze of the new BTs and paint a 6" red band and BT face red and nail USFS "BEARING TREE" and "LAND SURVEY MONUMENT" signs to all BTs.