

TOWNSHIP 25 RANGE 01E POINT IDENTIFIER # 500200

PRIMARY CORNER DESCRIPTION Cor. Secs. 26, 27, 34, & 35

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Joseph A Ganong & John G Collins, US Cadastral Engineers under instructions dated March 12, 1921, surveyed May 1927/June 1928 - (DCSO Records Vol. 21 Page(s) 9167)

Set an iron post, 3 ft. long, 2" dia., 27" in the ground, for cor. of secs. 26, 27, 34, & 35, with brass cap mkd

T25S R1E
S 27 | S 26
S 34 | S 35
1927

from which

- A pine, 48" dia., bears N.61°E., 54 lks., mkd: T25S R1E S26 BT.
- A fir, 16" dia., bears S.44°E., 6 lks., mkd: T25S R1E S35 BT.
- A fir, 10" dia., bears S.6°W., 34 lks., mkd: T25S R1E S34 BT.
- A fir, 30" dia., bears N.73°W., 36 lks., mkd: T25S R1E S27 BT.

R.C. Grant - DWP & JC Transit - 8/12/1957 - C.S. 42/328-1

From reference points set by Art Evans.

Set ¾" steel rod below surface of road, from which

Marked 40" Fir T25S R1E S34 2807. S.83°10'W., 200.4 ft.

Marked 8" Fir T25S R1E S27. N.87°30'W., 235.5 ft.

No other trees suitable for marking.

Note - See sketch in C.S. File

Bearing & distance information added 11/17/1997 - DCSO JC

Kristian DeGroot, PLS 1941 - For: USFS - Crew: Les Fanning, Matt Dixon, & Aaron Fanning - March 1998 - C.S. File 65/20-6

Found - 2" O.D. iron pipe buried 12" below the rock road surface of USFS Road 4713-500 with a 1927 2½" brass cap properly stamped.

No evidence of Grant's (1957)

Set - 2½"x30" aluminum monument, 26" in the ground with a ¾" aluminum cap stamped:

US DEPT. OF AGRICULTURE FOREST SERVICE

T25S R1E
S27 RM

S.29°E., 43.3

1997

PLS 1941

bears N.29°W., 43.3 ft.

continued next page

TOWNSHIP 25 RANGE 01E POINT IDENTIFIER # 500200

PRIMARY CORNER DESCRIPTION Cor. Secs. 26, 27, 34, & 35

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Chiseled "X B0" in 3" tall letters in a vertical rock face that bears S.13°E., 13.35 ft. to the center of the X.
5/8"x30" iron rod with plastic cap "BTS ENG-SUR" bears S.57°W., 45.7 ft.
9" D.Fir bears N.57°E., 35.1 ft. scribed "T25S R1E S26 BT" with a brass washer stamped "PLS 1941" nailed in lower blaze.
Painted a 6" red band and BT faces red and nail USFS "BEARING TREE" and "LAND SURVEY MONUMENT" signs to BTs.