

TOWNSHIP 25 RANGE 01E POINT IDENTIFIER # 500600

PRIMARY CORNER DESCRIPTION Cor. Secs. 2, 3, 10, & 11

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Joseph A Ganong & John G Collins, US Cadastral Engineers under instructions dated March 12, 1921, surveyed May 1927/June 1928 - (DCSO Records Vol. 22 Page(s) 9177)

Set an iron post, 3 ft. long, 2" dia., 27" in the ground, for cor. of secs. 2, 3, 10, & 11, with brass cap mkd

T25S R1E
S 3 | S 2
S 10 | S 11
1928

from which

- A fir, 6" dia., bears N.57 $\frac{3}{4}$ °E., 18 lks., mkd: T25S R1E S2 BT.
- A pine, 24" dia., bears S.4 $\frac{1}{2}$ °E., 60 lks., mkd: T25S R1E S11 BT.
- A cedar, 18" dia., bears S.54°W., 87 lks., mkd: T25S R1E S10 BT.
- A cedar, 20" dia., bears N.74 $\frac{1}{2}$ °W., 63 lks., mkd: T25S R1E S3 BT.