

TOWNSHIP 25 RANGE 01E POINT IDENTIFIER # 500700

PRIMARY CORNER DESCRIPTION Cor. Secs. 2, 3; 34 & 35 T24-1E

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Alonso Gesner, Deputy Surveyor, under contract No. 659, dated May 21, 1896 - (DCSO records Vol. 21 Pg 9103)

-----

Set basalt stone 14x8x8", 10" in the ground for cor. of secs. 34, 35, 2, & 3 mkd with 4 notches on W & 2 notches on E faces, from which

- A cedar, 12" dia., bears N.75°E., 36 lks., mkd: T24S R1E S35 BT.
- A fir, 8" dia., bears S.20°E., 30 lks., mkd: T25S R1E S2 BT.
- A fir, 36" dia., bears S.21°45'W., 35 lks., mkd: T25S R1E S3 BT.
- A cedar, 4" dia., bears N.41°W., 64 lks., mkd: T24S R1E S34 BT.

GLO survey by Joseph A Ganong & John G Collins, US Cadastral Engineers under instructions dated March 12, 1921, surveyed May 1927/June 1928 - (DCSO Records Vol. 21 Page(s) 9128)

-----

The cor. of secs. 2, 3, 34 and 35, which is a basalt stone, firmly set, 6x8x8" above ground, mkd with 4 notches on W., and 2 notches on E. edges; from which

- A cedar, 16" dia., bears N.75°E., 36 lks., marked T24S R1E S35 BT (Old BT)
- A fir, 10" dia., bears S.46½°E., 35 lks., marked T25S R1E S2 BT (New BT)
- A fir, 40" dia., bears S.21¾°W., 35 lks., marked T25S R1E S3 BT. (old BT)
- A cedar, 8" dia., bears N.41°W., 64 lks., marked T24S R1E S34 BT. (Old BT.)

The original bearing tree in sec. 2 is dead.