

PRIMARY CORNER DESCRIPTION S 1/4 Cor. Sec. 35 only; T24-1E

Alias	Description
_____	_____
_____	_____
_____	_____
_____	_____

GLO survey by Alonso Gesner, Deputy Surveyor, under contract No. 659, dated May 21, 1896 - (DCSO records Vol. 21 Pg 9104)

Set basalt stone, 20x10x4", 15" in the ground, on hillside, sloping South, for ¼ sec. cor. mkd. ¼ on N side, from which
A fir, 10" dia., bears S.45°30'E., 4 lks., mkd: ¼ S BT.
A madrone, 7" dia., bears N.33°E., 18 lks., mkd: ¼ S BT.

GLO survey by Joseph A Ganong & John G Collins, US Cadastral Engineers under instructions dated March 12, 1921, surveyed May 1927/June 1928 - (DCSO Records Vol. 21 Page(s) 9127)

The ¼ sec. cor. established for secs. 2 & 35, which is a basalt stone, 6x10x4" above ground, firmly set, marked ¼ on N. face.
I now change this cor. to refer to sec. 35 only.
Re-mark the stone ¼ S 35 on N. face; from which
A madrona, 12" dia., bears N.32°E., 16 lks., old B.T. with marks grown over.
A fir, 30" dia., bears S.44°E., 45 lks. (not 4), old BT, the marks on which I now destroy.
A fir, 10" dia., bears N.44°E., 42 lks., mkd ¼ S35 BT.
(New B.T.)

Dennis Gaylord, LS 1636, USFS & DCSO Deputy - Witness: Bill West - April 19, 1979 - C.S. file 60/24-38

Found - Orig. corner stone, which measures 20x14x5", is loosely set in the ground and is broken in half. Stone is marked "¼ 35".
A 30" D.Fir stump bears S.45°30'E., 29.7 ft. with a chopped out blaze as per 1928 record.
A down and decayed madrone, whose stump bears N.33°E., 11.88 ft. No marks visible.
A 14" D.Fir stump bears N.44°W., (not 44°E.) 25.9 ft. and 27.72 ft. slope distance. I open snag lying alongside this stump and find scribing "¼ S35 BT".
Set - Moving the corner stone aside, I set in its place a 1½"x36" iron pipe with a 2½" brass cap attached marked: T24S R1E ¼ S35 PLS 1636 1979
I bury corner stone alongside. From which:
A 26" D.Fir bears N.54°W., 70.2 ft. scribed "¼ S35 BT" on double blazes.
A 19" D.Fir bears N.24°E., 27.2 ft. scribed "¼ S35 BT" on double blazes.

continued next page

TOWNSHIP 25 RANGE 01E POINT IDENTIFIER # 541700

PRIMARY CORNER DESCRIPTION S 1/4 Cor. Sec. 35 only; T24-1E

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Note - Compass declination: 18°E. Corner ¼ S2 T25S R1E., bears west, 65.97 ft. (Rec. S.88°14'W., 96 lks or 63.36 ft.) USFS BT signs were placed on all BTs. Corner is about 50 ft. north of FS road No. 2512.

Lane Co. Surveyors Office - D. Michael Jackson - By: Bruce Bothel, Associate Surveyor & John Randall, Engineering Tech 1 - Sept. 13, 2007 - C.S. File 65/76-44

Found - 2½" brass cap dated 1979 in a stone mound, and mkd: "PLS 1636"
A 30" rotten fir stump with a chopped out face brs S.44°10'E., 29.7' (S.45°30'E., 29.7') 1898
A 14" rotten fir stump with "¼ S35 BT" fd. in loose slab brs N.43°10'W., 26.6' (N.44°E., 27.7') 1928
A 2½" brass cap marking the North ¼ cor. of sec. 2 only brs S.89°41'40"W., 65.65' (S.88°14'W., 63.4') 1928
A 34" D.Fir with a healed face brs N.53°06'W., 70.4' (N.54°W., 70.2') 1979
A 26" D.Fir with a healed face brs N.24°30'E., 27.0' (N.24°E., 27.2') 1979
New - 2" alum. cap "LCSO-RP1-2007" a top a 5/8x30" rebar brs S.16°27'E., 11.47'
All distances shown are to center unless otherwise noted.

Geographic Map Location (NAD 83/91 Values) - Use for navigating to corner area - not of survey grade accuracy. Lat: 43°26'17.1" Long: 122°39'07.5"