

TOWNSHIP 25 RANGE 01E POINT IDENTIFIER # 600600

PRIMARY CORNER DESCRIPTION Cor. Secs. 1, 2, 11, & 12

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by Joseph A Ganong & John G Collins, US Cadastral Engineers under instructions dated March 12, 1921, surveyed May 1927/June 1928 - (DCSO Records Vol. 21 Page(s) 9164)

-----  
Set an iron post, 3 ft. long, 2" dia., 27" in the ground, for cor. of secs. 1, 2, 11, & 12, with brass cap mkd

T25S R1E  
S 2 | S 1  
S 11 | S 12  
1928

from which

- A fir, 12" dia., bears N.57½°E., 38 lks., mkd: T25S R1E S1  
BT.
- A fir, 14" dia., bears S.30°E., 44 lks., mkd: T25S R1E S12  
BT.
- A fir, 12" dia., bears S.49°W., 25 lks., mkd: T25S R1E S11  
BT.
- A fir, 15" dia., bears N.30°W., 117 lks., mkd: T25S R1E S2  
BT.