

TOWNSHIP 25 RANGE 01E POINT IDENTIFIER # 600700

PRIMARY CORNER DESCRIPTION C C Secs. 1 & 2 only

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Joseph A Ganong & John G Collins, US Cadastral Engineers under instructions dated March 12, 1921, surveyed May 1927/June 1928 - (DCSO Records Vol. 21 Page(s) 9126-7)

Set an iron post, 3 ft. long, 2" dia., 27" in the ground, for closing cor. of secs. 1 & 2, with brass cap mkd

T24S R1E
S 35

S 2 | S 1
T25S | R1E
C C
1928

from which

- A fir, 16" dia., bears S.63°E., 55 lks., mkd: T25S R1E S1
C C BT.
- A fir, 18" dia., bears S.26½°W., 45 lks., mkd: T25S R1E S2
C C BT.

Dennis Gaylord, LS 1636, USFS & DCSO Deputy - Witness: Bill West - April 19, 1979 - C.S. file 60/24-37

Found - 2" Iron pipe firmly set & protruding 14" above ground. A 2½" brass cap attached to the pipe is marked: US GLO survey R1E T24S S35 C C S2 S1 T25S R1E 1928.

- A 37" D.Fir bears S.63°E., 36.3 ft. & has a single healed blaze.
- A 28" D.Fir bears S.26°30'W., 29.7 ft. & has a single healed blaze.

USFS bearing tree signs were placed on both BTs and they were painted with a band of red paint. No new Accessories.

The corner S35|S36 bears N.89°30'E., 57.3 ft Rec. N.89°02'E., 0.86 chs.) S 1

Corner lies 5 ft. north of FS Road #2512.