

PRIMARY CORNER DESCRIPTION US Location monument #2

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

MS No 501, Olive Placer Claim, by Chas. M. Collier, US Deputy Mineral Surveyor, under instructions dated Oct. 20, 1902, Surveyed Oct./Nov. 1902 - (DCSO Records C.S. 57/38 (pg 6))

-----

In survey No. 501, Olive Placer Claim, was found to be more than two miles from any corners of the US government surveys or any previously established monument. I therefore proceeded to establish a mineral monument in connection with said survey.

I set a post 8 ft. long 7" square 36" in the ground, scribed U.S.L.M.2 with tack driven in the top at point for connection, protected by well built conical mound of stones of 6 ft. base 3 ft. high around it, from which

A fir 28" dia., bears N.73°W., 24.3 ft

A fir 24" dia., bears S.35°50'W., 6.1 ft.

Each faced & scribed U.S.L.M.2 BT with exact bearing point being indicated on face by scribing a cross \_\_\_?\_\_\_.

GLO survey by Joseph A Ganong & John G Collins, US Cadastral Engineers under instructions dated March 12, 1921, surveyed May 1927/June 1928 - (DCSO Records Vol. 21 Page(s) 9156)

-----

USLM No 2, which is a fir post, 7" sq., top beveled, extended 2½ ft. above a mound of stone, 6 ft. base, 3 ft. high, firmly set, marked USLM No. 2 on S side, from which a fir, 24" dia., bears N.73°W., 37 lks., with marks grown over and a fir, 24" dia., bears S.35¾°W., 9 lks., with marks grown over, bears S.55°14'E., 22.01 chs. from cor. Secs. 23, 24, 25 & 26

Douglas Co. Surveyors Office - Gary Langlitz - M. Lenora Ladig - A. Vic Cangie - 9/10/1975 - C.S. File 57/38 & M58-23

-----

Found - Rotted remains of 7" square wooden post, no marks remaining, supported in a mound of rock 6 ft. in dia. at the base and 3 ft. high From which

An orig. 22" now 28" D.Fir bears N.73°W., 24.3 ft. alive and well-healed.

An orig. 24" now 36" D.Fir bears S.35°50'W., 6.1 ft. alive and well-healed We remove the remains of the wooden post and replace it with a 1x30" IP supported its full length in the rock mound, with brass cap attached, mkd: T25S R1E

DOUGLAS CO. SURVEYOR +  
1975 U S L M 2

Note - This corner lies between Steamboat Creek & Steamboat creek forest RD.

Magnetic Declination: 20° East