

TOWNSHIP 25 RANGE 01E POINT IDENTIFIER # 639700

PRIMARY CORNER DESCRIPTION S 1/4 Cor. Sec. 36 only; T24-1E

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Alonso Gesner, Deputy Surveyor, under contract No. 659, dated May 21, 1896 - (DCSO records Vol. 21 Pg 9105)

Set basalt stone 12x10x8", 8" in the ground for ¼ sec. cor. mkd. ¼ on N face, from which

A W.Fir, 12" dia., bears N.51°E., 22 lks., mkd: ¼ S BT.

A hemlock, 12" dia., bears S.41°W., 72 lks., mkd: ¼ S BT.

GLO survey by Joseph A Ganong & John G Collins, US Cadastral Engineers under instructions dated March 12, 1921, surveyed May 1927/June 1928 - (DCSO Records Vol. 21 Page(s) 9125)

The ¼ sec. cor. established for secs. 1 & 36, which is a basalt stone, 6x10x8" above ground, firmly set, marked ¼ on N face.

I now change this cor. to refer to sec. 36 only.

Re-mark the stone ¼ S36 on N face; from which

A fir, 26" dia., bears N.75°E., 24 lks., mkd: ¼ S36 BT.
(New BT)

A hemlock, 16" dia., bears S.41°W., 72 lks., old BT, the marks on which I now destroy.

A fir, 24" dia., bears N.69½°W., 134 lks., mkd ¼ S36 BT
(New BT)

The old BT is sec. 36 is dead.