

Alias	Description
_____	_____
_____	_____
_____	_____
_____	_____

GLO survey by Joseph A Ganong & John G Collins, US Cadastral Engineers under instructions dated March 12, 1921, surveyed May 1927/June 1928 - (DCSO Records Vol. 21 Page(s) 9147-8)

Set an iron post, 3 ft. long, 2" dia., 27" in the ground, for cor. of secs. 13, 18, 19, & 24, with brass cap mkd

T25S
R1E|R2E
S 13|S 18
S 24|S 19
1927

from which

- A fir, 18" dia., bears N.31°E., 49 lks., mkd: T25S R2E S18 BT.
- A fir, 40" dia., bears S.28°E., 15 lks., mkd: T25S R2E S19 BT.
- A cedar, 14" dia., bears S.49°W., 78 lks., mkd: T25S R1E S24 BT.
- A fir, 12" dia., bears N.38°W., 78 lks., mkd: T25S R1E S13 BT.

Jim Landrum, USFS & Deputy, Doug. Co. Surveyors Office - Leonard Herzstein, Witness - May 10, 1983 - C.S. 62/10-2

Found - 1927 GLO brass cap, properly marked, on 2" dia. iron post, firmly set, projecting 6" above ground, leaning westerly, Used the point where the I.P. comes out of the ground as the corner point.

Orig. 26" D.Fir, stump, N.31°E., 31.9 ft. (Rec. 32.3 ft.) with healed blaze.

Orig. 44" D.Fir, S.28°E., 9.9 ft. with healed blaze.

A roothole, N.38°W., 51.5 ft. with 14" D. fir log alongside with fragmentary scribe marks visible on partially healed blaze.

New BTs- 12" maple, N.78°E., 29.2 ft. scribed "T25S R2E S18 CS BT" on single blaze.

5" W.Fir, S.73°W., 26.8 ft. scribed "T25S R1E S24 CS BT" on single blaze.

40" D.Fir, N.70°W., 38.3 ft. scribed "T25S R1E S13 CS BT" single blaze. (Blaze is on old logging scar.)

Note - Corner is approx. 250 ft. S of USFS Rd. #3811-100 in the NW corner of clearcut unit #25-2E-19-5. Corner is about 66 ft. north of creek.