

TOWNSHIP 25 RANGE 01E POINT IDENTIFIER # 700500

PRIMARY CORNER DESCRIPTION Cor. Secs. 12, 13, 7 & 18 T25-2E

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by Joseph A Ganong & John G Collins, US Cadastral Engineers under instructions dated March 12, 1921, surveyed May 1927/June 1928 - (DCSO Records Vol. 21 Page(s) 9149)

-----  
Set an iron post, 3 ft. long, 2" dia., 27" in the ground, for cor. of secs. 7, 12, 13, & 18, with brass cap mkd

T25S	
R1E	R2E
S 12	S 7
S 13	S 18
1928	

from which

- A cedar, 7" dia., bears N.76½°E., 32 lks., mkd: T25S R2E S7 BT.
- A fir, 12" dia., bears S.5°E., 60 lks., mkd: T25S R2E S18 BT.
- A fir, 24" dia., bears S.22°W., 17 lks., mkd: T25S R1E S13 BT.
- A cedar, 8" dia., bears N.48°W., 30 lks., mkd: T25S R1E S12 BT.