

PRIMARY CORNER DESCRIPTION Corner #4 MS #501

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Mineral Survey No. 501, Olive Placer Claim, by Chas. M. Collier, US Deputy Mineral Surveyor, under instructions dated Oct. 20, 1902, Surveyed Oct./Nov. 1902 - (DCSO Records C.S. File 57/38)

A post 4½ ft. long 4" sq. Set 18" in the ground scribed 4-501 whence
 A fir 36" dia., bears N.62°W., 26 ft.
 A fir 18" dia., bears S.16°W., 24 ft.
Each blazed and scribed 4-501 BT

Douglas Co. Surveyors Office - Gary Langlitz - Lenora Lading - Vic Cangie - 9/8/1975 - C.S. File 57/38 - M58-23

Found - Orig. 36" now 42" D.Fir, alive and well-healed bears N.60¼°W., 26.0 ft. (N.62°W., 26.0 ft)
 An orig. 18" now 30" D.Fir, alive and well-healed, bears S.14°W., 24.0 ft. rec. S.16°W., 24.0 ft.)
At the corner point - We set a 1x30" IP with brass cap attached, marked: T25S R1E
 DOUGLAS CO. SURVEYORS
 1975 MS | COR 4
Compass declination 20° East 501

Douglas Co. Surveyors Office - Randall W. Smith - Stephen J. Flause - Dec. 9, 1985 - C.S. File 62/29-5

Found - A Doug. Co. brass disk on an IP protruding 7" above ground marked as noted in 1975 ren.
 An orig. BT, 36" now 39" 3½ ft. high D.Fir stump with a partial well healed lower blaze, bears N.60¼°W., 26.0 ft. agrees with 1975 ren. (Rec. N.62°W., 26.0 ft.)
 An orig. BT, a 18" now 33" dia., 7 ft. high D.Fir stump with a single fully healed blaze, bears S.14°W., 24.0 ft. agrees with 1975 ren. (Rec. orig. S.16°W., 24.0 ft.) This BT will be lowered to 2 ft. by May 1986 per Ron Murphy, N. Umpqua River District.
New BTs- 12" D.Fir double blazed & scribed "4 MS 501 CS BT" bears N.2°W., 26.7 ft.
 12" D.Fir double blazed & scribed "4 MS 501 CS BT" bears S.61°W., 27.5 ft.
Corner lies at west end of Steamboat Falls Campground near picnic tables.