

TOWNSHIP 25 RANGE 01 POINT IDENTIFIER # 100147

PRIMARY CORNER DESCRIPTION Sec. Cor. for 25 & 36 only, T25-2

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GL0 survey by John A. McQuinn, Deputy Surveyor, under Contract #466, dated April 5, 1883 (DCSO records Vol. 8 Page(s) 3475-76)

Set post 4½ ft. long, 4" sq., 24" in ground for cor. to secs. 25, 30, 31 and 36, marked T25S S30 on NE.; R1W S31 on SE.; R2W S36 on SW.; and S25 on NW. faces, with 5 notches on N. and 1 notch on S. edges, from which

- A Fir 18" dia., bears N.40°E., 15 lks. dist. mkd. T25S R1W S30 BT.
- A Fir 18" dia., bears S.44°E., 33 lks. dist. mkd. T25S R1W S31 BT.
- A Fir 22" dia., bears S.28°W., 46 lks. dist. mkd. T25S R2W S36 BT.
- A Fir 12" dia., bears N.61°W., 16 lks. dist. mkd. T25S R2W S25 BT.

GL0 survey by Hezekiah H. Johnson, Deputy Surveyor, under Contract #721, dated May 1, 1900 - (DCSO records Vol. 8 Page(s) 3492 and 3493-94)

(Page 3492)
No trace of the cor. of secs. 25, 30, 31 and 36 can be found. (Pgs. 3493-94)
A Hemlock 6" dia. for cor. of secs. 25, 30, 31 and 36, I mark T25S S30 on NE.; R1W S31 on SE.; S36 on SW. and R2W S25 on NW. sides, with 5 notches on N. and 1 notch on S. sides, from which

- A Hemlock 6" dia., bears N.29°E., 26 lks. dist. mkd. T25S R1W S30 BT.
- A Fir 30" dia., bears S.26°E., 31 lks. dist. mkd. T25S R1W S31 BT.
- A Fir 6" dia., bears S.25°W., 65 lks. dist. mkd. T25S R2W S36 BT.
- A Fir 6" dia., bears N.35°30'W., 27 lks. dist. mkd. T25S R2W S25 BT.

Glen McChesney - For: Weyerhaeuser Co. - June 2, 1959 - C.S. File 53/112-48

Found - Orig. 6" Hemlock corner tree, now 12", old face, squared.
8" Hemlock, N.29°E., 26 lks. (17.2 ft.), rotten remains, down Hemlock, marks should have been obliterated by 1900 survey.
36" Fir, S.26°E., 31 lks. (20.5 ft.), now 44", face not opened. Marks should have been obliterated by 1900 survey. (Cont. Next Page)

TOWNSHIP 25 RANGE 01 POINT IDENTIFIER # 100147

PRIMARY CORNER DESCRIPTION Sec. Cor. for 25 & 36 only, T25-2

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Survey by Glenn Baughman - For: Weyerhaeuser Co. - Aug. 1975
(filed June 1979) - M 77-57

Found - 56" Fir, face grown over, bears S.26°E., 20.5 ft.
Original BT.
17" Hemlock with visible scribe. (down) Orig. BT.
8" Fir bears S.25°W., 42.9 ft., Orig. BT.
10" Fir bears S.43°W., 30.3 ft. (DCSO BT.)
10" Fir bears N.48°W., 20.5 ft.
All trees previously opened, scribes still visible.
SET Brass cap.

Fd. & used on BLM resurvey by A. Bert Skeesick, Cadastral
Surveyor under Group #1979, surveyed 2001/2002- (DCSO rec.
Vol. 54 Page(s) 20900-1)

Douglas Co. Surveyors Office - Crew: Stephen Flause & Jeff
Lorsung- 3/30/2022 (Filed 7/21/2022) - C.S. File 67/52-30

Found - 2½" brass cap (properly mkd) on I. Pipe proj. 6"
Orig. BT
Burnt 57" Fir S.22°E. 19.6 ft (rec. S.26°E. 19.5 ft)
DCSO BT 1967
28"x2' sawn burnt stump S.45°W., 30.2 ft. (rec
S.43°W., 30.3 ft) PK top center.
Baughman BT
29" double trunk Hemlock (rec 10" Fir) N.43½°W.,
20.8 ft. (rec. N.48°W., 20.5 ft) brass washer
added in face. PK nail right side center.
New - Burnt-dead 45" Fir N.34°E., 50.7 ft. Brass washer n
old face, PK nail right side center.
Note - Area burnt 9/2020
Compass decl. 14½°E.
See sketch in file.
Lat: Lat: 43°21'27.99"N Long: 122°52'25.49"W