

PRIMARY CORNER DESCRIPTION E. 1/4 Cor. for Sec. 25 only, T25-2

Alias	Description
Alias	Description
Alias	Description
Alias	Description

GLO survey by John A. McQuinn, Deputy Surveyor, under Contract #466, dated April 5, 1883 (DCSO records Vol. 8 Page(s) 3476)

Set post 3 ft. long, 3" sq., 24" in ground for ¼ sec. cor. marked ¼ S. on W. face, from which
A Sugar Pine 36" dia., bears West, 42 lks. dist., mkd. ¼ S BT.
A Laurel 4" dia., bears S.20°E., 6 lks. dist. mkd. ¼ S BT.

GLO survey by Hezekiah H. Johnson, Deputy Surveyor, under Contract #721, dated May 1, 1900 - (DCSO records Vol. 8 Page(s) 3493 and 3494)

(page 3493)
Find no trace of any line or corners.
(page 3494)
Set a basalt stone 18x10x8 ins., 12" in the ground for ¼ sec. cor. mkd. ¼ on W. face, from which
A Cedar 16" dia., bears N.71°E., 31 lks. dist. mkd. ¼ S30 BT.
A Hemlock 4" dia., bears N.39°W., 24 lks. dist. mkd. ¼ S25 BT.

V.W. Hosford, May 1949/Oct. 1950 - C.S. File 40/279

At this point, I set a 1½" I.P. with steel cap, from which
A Fir 24" dia., bears S.11½°W., 58.6 ft. mkd. T25S R2W ¼ S25 P.S. 253 BT.
A Fir 24" dia., bears N.55½°W., 37.7 ft. mkd. T25S R2W ¼ S25 P.S. 253 BT.

Corner used and accepted in BLM resurvey by James E. Jelley, Cadastral Surveyor, under Group #'s 350 and 929 - Surveyed May 1978/May 1980 - (DCSO records Vol. 42 Page(s) 16329)

BLM resurvey by A. Bert Skeesick, Cadastral Surveyor under Group #1979, surveyed 2001/2002- (DCSO rec. Vol. 54 Page(s) 20902)

The ¼ sec. cor. of sec. 25 only, monumented with an iron pipe, 1½" dia., firmly set, projecting 5" above ground, with steel cap, no marks visible, from which the remains of bearing trees mkd. by Hosford, in 1950, & reported by Jelley
A roothole, bears S.11½°W., 58.1 ft., with fallen fir trunk, 36" dia., lying alongside, with healed blaze.
A fir, 28" dia., bears N.55½°W., 37.6 ft., with healed blaze.

TOWNSHIP 25 RANGE 01 POINT IDENTIFIER # 100207

PRIMARY CORNER DESCRIPTION E. 1/4 Cor. for Sec. 25 only, T25-2

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

and new bearing tree

A hemlock, 9" dia. bears S.15¼°W., 21.5 ft., mkd. ¼ S25 BT

Each new bearing tree has a 2½"x ¼" magnetic nail (Mag Nail) driven at the base right side-center.