

PRIMARY CORNER DESCRIPTION Sec. Cor. for 24 & 25 only, T25-2

Alias	Description
Alias	Description
Alias	Description
Alias	Description

GLO survey by John A. McQuinn, Deputy Surveyor, under Contract #466, dated April 5, 1883 (DCSO records Vol. 8 Page(s) 3976-77)

Set post 4½ ft. long, 4" sq., 24" in ground for cor. to secs. 19, 24, 25 and 30, marked T25S S19 on NE.; R1W S30 on SE.; S25 on SW.; and R2W S24 on NW. faces, with 4 notches on N. and 2 notches on S. edges, from which

- A Hemlock 8" dia., bears S.85°E., 19 lks. dist. mkd. T25S R1W S30 BT.
- A Cedar 18" dia., bears N.84°W., 16 lks. dist. mkd. T25S R2W S24 BT.
- A Hemlock 12" dia., bears N.35°E., 12 lks. dist. mkd. T25S R1W S19 BT.
- A Hemlock 24" dia., bears S.74°W., 35 lks. dist. mkd. T25S R2W S25 BT.

GLO survey by Hezekiah H. Johnson, Deputy Surveyor, under Contract #721, dated May 1, 1900 - (DCSO records Vol. 8 Page(s) 3493 and 3495)

(Page 3493)

Find no trace of any line or corners.

(Page 3495)

Set a basalt stone 17x11x8 ins., 12" in the ground for cor. of secs. 19, 24, 25, and 30, marked with 4 notches on N. and 2 notches on S. edges, from which

- A Hemlock 4" dia., bears N.21°E., 16 lks. dist. mkd. T25S R1W S19 BT.
- A Hemlock 5" dia., bears S.48°E., 29 lks. dist. mkd. T25S R1W S30 BT.
- A Fir 12" dia., bears S.32°W., 60 lks. dist. mkd. T25S R2W S25 BT.
- A Cedar 6" dia., bears N.24°W., 68 lks. dist. mkd. T25S R2W S24 BT.

V. W. Hosford, O.L.S. #253 - April 1949/Oct. 1950 - C.S. File 40/279 and M 12-61

I set a 1½" I.P. with steel cap, from which

- A Fir 32" dia., bears S.78½°W., 35.9 ft. mkd. T25S R2W S25 P.S. 253 BT.
- A Fir 30" dia., bears N.39°W., 16.4 ft. mkd. T25S R2W S24 P.S. 253 BT.

(Cont. Next Page)

PRIMARY CORNER DESCRIPTION Sec. Cor. for 24 & 25 only, T25-2

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Glen McChesney - For: Weyerhaeuser - 7/30/1958 - C.S. 53/112

 Hosford's corner found OK. Added "W" nails and plates to Hosford BTs.

Douglas Co. Surveyors Office - L.E. Monrean, Deputy - K. Cheney, crew - June 10, 1976 - C.S. File 59/15

 Found - A 1½" Iron pipe with steel cap.
 A Fir 32", now 38" stump, bears S.78½°W., 37.0 ft. to center and 35.7 ft. to face. (Rec. 35.9 ft.)
 Stump is scribed "T25S R2W S25 P.S. 253 BT".
 I removed iron pipe and steel cap and replace with a brass cap at ¼ corner, stamped: Douglas County Surveyors office

	T	25	S	
R		S 24		S30
2		S 25		1
W		1976		W

New BT - A 10" Hemlock bears S.50°W., 121.9 ft. Tree double blazed and scribed "T25S R2W S25 CS BT".

Corner Found and Used in BLM resurvey by James E. Jelley, Cadastral Surveyor, under Group #'s 350 and 929 - Surveyed May 1978/May 1980 - (DCSO records Vol. 42 Page(s) 16329-30)

BLM resurvey by A. Bert Skeesick, Cadastral Surveyor under Group #1979, surveyed 2001/2002- (DCSO rec Vol. 54 Pg 20903)

 The cor. of secs. 24 & 25 only, monumented with an iron post, 1½" dia., firmly set, projecting 7" above ground, in a mound of stone, 2½ ft. base, to top, with brass cap (properly) mkd. from which the remains of BTs mkd. by Hosford, in 1950, & reported by Jelley

A fir stump, 31" dia., bears S.78½°W., 37.9 ft., with scribe marks 25S R2 visible on partially healed blaze. (Record, 36.0 ft.)

A fir stump, 30" dia. bears N.39°W., 16.5 ft., with scribe marks S24 PS 53 visible on partially healed blaze.

and bearing tree mkd. by Monrean, in 1976. Jelley reports this tree as being mkd. by Francis Ingram.

A hemlock, 20" dia., bears S.47¾°W., 121.8 ft., with healed double blaze. (Record, S.50°W.)

and new bearing tree

A fir, 6" dia. bears N.9¾°W., 6.2 ft. mkd. T25S R2W S24 BT

Each new bearing tree has a 2½"x ¼" magnetic nail (Mag Nail) driven at the base right side-center.