

Alias	Description
Alias	Description
Alias	Description
Alias	Description

GLO survey by John A. McQuinn, Deputy Surveyor, under Contract #466, dated April 5, 1883 (DCSO records Vol. 8 Page(s) 3478)

Set post 3" sq., 3 ft. long, 24" in ground for ¼ sec. cor. mkd. ¼ S on W. face, from which
A Fir 6" dia., bears S.63°E., 14 lks. dist. mkd. ¼ S BT.
A Fir 8" dia., bears S.70°W., 18 lks. dist. mkd. ¼ S BT.

GLO survey by Hezekiah H. Johnson, Deputy Surveyor, under Contract #721, dated May 1, 1900 - (DCSO records Vol. 8 Page(s) 3493 and 3496-97)

(Page 3493)
Find no trace of any line or corners.
(Pages 3496-97)
Set a basalt stone 15x9x7 ins., 10" in the ground for ¼ sec. cor. mkd. ¼ on W. face, from which
A Fir 6" dia., bears N.60°E., 12 lks. dist. mkd. ¼ S18 BT.
A Hemlock 4" dia., bears N.12°W., 50 lks. dist. mkd. ¼ S13 BT.

V. W. Hosford, Surveyor - May 1949/Oct. 1950 - C.S. File 40/279 and M 12-61

I set a 2" I.P. with steel cap, from which
A Yew 8" dia., bears N.65°W., 20.0 ft. mkd. T25S R2W ¼ S13 P.S. 253 BT.
A Cedar 8" dia., bears N.18°W., 12.2 ft. mkd. T25S R2W ¼ S13 P.S. 253 BT.

BLM resurvey by James E. Jelley, Cadastral Surveyor, under Group #'s 350 and 929 - Surveyed May 1978/May 1980 - (DCSO records Vol. 42 Page(s) 16333-34)

Point for the ¼ sec. cor., at proportionate distance; there is no remaining evidence of the original corner.
Set an iron post, 28" long, 2 1/2" dia., 24" in the ground, with brass cap mkd:
T 25 S*
¼ *
S 13*
R 2 W*
1978

from which a bearing tree of which I have no record:
A Fir 10" dia., bears S.18°E., 30½ lks. dist. with scribe marks ¼ S18 BT visible on open blaze.
(Cont. Next Page)

TOWNSHIP 25 RANGE 01 POINT IDENTIFIER # 100407

PRIMARY CORNER DESCRIPTION E. 1/4 Cor. for Sec. 13 only, T25-2

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

and new bearing trees:

A Fir 3" dia., bears S.60¼°W., 42 lks. dist., mkd. X BT.

A Fir 16" dia., bears N.12½°W., 86½ lks. dist. mkd. ¼ S13
BT.

Fd. & used on BLM resurvey by A. Bert Skeesick, Cadastral Surveyor under Group #1979, surveyed 2001/2002- (DCSO rec. Vol. 54 Page(s) 20905)

Ron Rice - For: Seneca Jones Timber Co. & Roseburg Resources Co. - Aug. 2012 - C.S. File 65/75-9

Found - 3¼" BLM Brass cap dated 1978 with the following accessories:

34" D.Fir bears S.18°E., 20.1' - healed face.

21" D.Fir bears S.58¼°W., 28.6' - healed face.

36" D.Fir bears N.15½°W., 57.1' - healed face.